

draw-out molded case circuit breaker without guide frame frame 1600; with RTC and 4AUX trip alarm switch S24; Icu "M" Icu=55kA @ 415V, 3-pole ETU650, LSI, In=800A display, meas., comm. function Ir=320...800A Isd=0.6...10xIn, li=1.5...15xIn N conductor protec. adjustable opt. w. ext. CT; up to 200% main contacts f. draw-out vers. With optional communication connection including integrated breaker connect 24 V DC module, actuator COM ACT, COM RTC and COM PSS(as draw-out version) with Metering MF Basic for energy monitoring Voltage tap at the top Motorized operating mechanism 220...250 V AC/DC incl. S21 spring energy store signaling switch With electr. and mech. calling Switch-on solenoid (CC) 220-240 V AC/DC without 2nd auxiliary release With 1st auxiliary release, ST Shunt release 220-240 V AC/DC F03= F03= Communication module COM041 Communication module COM041 PROFINET Gateway PROFINET Gateway S08= Ronis locking device in OFF position, against unauthorized switching on (Safe Off/disconnector function)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA2780-1DE30-4HA7-Z F03+S08>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VA2780-1DE30-4HA7-Z F03+S08>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA2780-1DE30-4HA7-Z F03+S08

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



last modified:

7/18/2024

