## 3VA4135-6ED34-0AA0

Data sheet



circuit breaker 3VA4 UL frame 125 breaking capacity class H 65kA @ 480 V 3-pole, line protection TM210, FTFM, In=35A overload protection Ir=35A fixed short-circuit protection Ii=10 x In clamp connection

Model		
product brand name	SENTRON	
product designation	Molded-case circuit breaker	
product designation / according to UL file	HEAB	
design of the product	System protection	
design of the load switch / according to UL 489 / Heating, Air Conditioning, and Refrigeration circuit breaker (HACR Type)	Yes	
design of the load switch / according to UL 489 / High-Intensity- Discharge circuit breaker (HID Type)	Yes	
design of the load switch / according to UL 489 / Switching Duty circuit breaker (SWD Type)	No	
design of the overcurrent release	TM210	
protection function of the overcurrent release	Ц	
number of poles	3	
General technical data		
operating voltage / at AC / rated value	690 V	
power loss [W] / maximum	9.7 W	
power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	3.23 W	
mechanical service life (operating cycles) / typical	15 000	
electrical endurance (operating cycles) / at 480 V	8 000	
electrical endurance (operating cycles) / at 600 V	4 000	
product feature / for neutral conductors / upgradable/retrofittable / short-circuit and overload proof	No	
ground-fault monitoring version	Without	
product function		
<ul> <li>communication function</li> </ul>	No	
other measurement function	No	
Net Weight	0.743 kg	
Current		
marking / according to UL 489 / 100%-rated breaker	No	
operational current		
• at 40 °C	35 A	
• at 45 °C	34 A	
• at 50 °C	33 A	
• at 55 °C	33 A	
• at 60 °C	32 A	
• at 65 °C	31 A	
● at 70 °C	30 A	
Switching capacity according to IEC 60947		
switching capacity class of the circuit breaker	Н	
design of short-circuit protection	For switching power values in DC networks, see the 3VA molded case circuit	

	breaker device manual; link to chapter	be found under Service & Support in the last	
Switching capacity according to UL 489			
current breaking capacity			
● at 240 V	100 kA		
● at 480 Y/277 V	65 kA		
● at 480 V	65 kA		
● at 600 Y/347 V	25 kA		
Adjustable parameters			
adjustable response value delay time (tr) / for L-tripping / with I2t characteristic			
• minimum	1 s		
• maximum	1 s		
product function / grounding protection	No		
Mechanical Design			
product component			
undervoltage release	No		
<ul> <li>voltage trigger</li> </ul>	No		
trip indicator	No		
height [in]	5.09 in		
height	129.4 mm		
width [in]	3 in		
type of connectable conductor cross-sections / of the round conductor terminal / stranded	1 x (14 AWG - 8 AWG)		
width	76.2 mm		
depth [in]	2.96 in		
depth	75.1 mm		
Connections			
arrangement of electrical connectors / for main current circuit	output side: circular conductor	connection	
type of electrical connection / for main current circuit	Infeed side: Low tab		
design of the surface / of the connections / on the bottom of the switch (N, 2, 4, 6)	Tin		
Auxiliary circuit			
number of CO contacts / for auxiliary contacts	0		
Accessories			
product extension / optional / motor drive	No		
Environmental conditions			
protection class IP / on the front	IP40		
ambient temperature			
during operation / minimum	-25 °C		
during operation / maximum	70 °C		
during storage / minimum	-40 °C		
during storage / maximum	80 °C		
Certificates			
General Product Approval	EMC	other	



Miscellaneous





Miscellaneous

Confirmation

other

Miscellaneous

Further information

Siemens has decided to exit the Russian market (see here). https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business

Siemens is working on the renewal of the current EAC certificates

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

https://support.industry.siemens.com/cs/ww/en/view/109813875

Information- and Downloadcenter (Catalogs, Brochures,...)

http://www.siemens.com/lowvoltage/catalogs

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA4135-6ED34-0AA0

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3VA4135-6ED34-0AA0


Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...) http://www.automation.siemens.com/bilddb/cax\_en.aspx?mlfb=3VA4135-6ED34-0AA0


CAx-Online-Generator


http://www.siemens.com/cax


**Tender specifications** 


http://www.siemens.com/specifications











last modified: 4/20/2023 🖸