



circuit breaker 3VA4 UL Frame 125 breaking capacity class H 65 kA @ 480 V 2-pole, line protection TM210, FTFM, $I_n=70$ A overload protection $I_r=70$ A permanently set short-circuit protection $I_i=10 \times I_n$

Model	
product brand name	SENTRON
product designation	Molded-case circuit breaker
product designation / according to UL file	HEAB
design of the product	System protection
design of the load switch / according to UL 489 / Heating, Air Conditioning, and Refrigeration circuit breaker (HACR Type)	Yes
design of the load switch / according to UL 489 / High-Intensity-Discharge circuit breaker (HID Type)	No
design of the load switch / according to UL 489 / Switching Duty circuit breaker (SWD Type)	No
design of the overcurrent release	TM210
protection function of the overcurrent release	LI
number of poles	2
General technical data	
operating voltage / at AC / rated value	415 V
power loss [W] / maximum	10.7 W
power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	5.35 W
mechanical service life (operating cycles) / typical	15 000
electrical endurance (operating cycles) / at 480 V	8 000
electrical endurance (operating cycles) / at 600 V	4 000
product feature / for neutral conductors / upgradable/retrofitable / short-circuit and overload proof	No
ground-fault monitoring version	Without
product function	
• communication function	No
• other measurement function	No
Net Weight	0.514 kg
Current	
marking / according to UL 489 / 100%-rated breaker	No
operational current	
• at 40 °C	70 A
• at 45 °C	69 A
• at 50 °C	68 A
• at 55 °C	67 A
• at 60 °C	65 A
• at 65 °C	64 A
• at 70 °C	63 A
Switching capacity according to IEC 60947	
switching capacity class of the circuit breaker	H
design of short-circuit protection	For switching power values in DC networks, see the 3VA molded case circuit

		breaker device manual; link to be found under Service & Support in the last chapter
Switching capacity according to UL 489		
current breaking capacity		
• at 240 V		100 kA
• at 480 Y/277 V		65 kA
• at 480 V		65 kA
• at 600 Y/347 V		25 kA
Adjustable parameters		
adjustable response value delay time (tr) / for L-tripping / with I2t characteristic		
• minimum		1 s
• maximum		1 s
product function / grounding protection		No
Mechanical Design		
product component		
• undervoltage release		No
• voltage trigger		No
• trip indicator		No
height [in]		5.09 in
height		129.4 mm
width [in]		2 in
type of connectable conductor cross-sections / of the round conductor terminal / stranded		1 x (8 AWG - 3/0)
width		50.8 mm
depth [in]		2.96 in
depth		75.1 mm
Connections		
arrangement of electrical connectors / for main current circuit		output side: circular conductor connection
type of electrical connection / for main current circuit		Infeed side: Low tab
design of the surface / of the connections / on the bottom of the switch (N, 2, 4, 6)		Tin
Auxiliary circuit		
number of CO contacts / for auxiliary contacts		0
Accessories		
product extension / optional / motor drive		No
Environmental conditions		
protection class IP / on the front		IP40
ambient temperature		
• during operation / minimum		-25 °C
• during operation / maximum		70 °C
• during storage / minimum		-40 °C
• during storage / maximum		80 °C
Approvals / Certificates		
General Product Approval	EMV	other

[Miscellaneous](#)



[Miscellaneous](#)

[Confirmation](#)

[Miscellaneous](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA4170-6ED24-3AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)


<https://support.industry.siemens.com/cs/ww/en/ps/3VA4170-6ED24-3AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA4170-6ED24-3AA0

CAX-Online-Generator

<http://www.siemens.com/cax>



last modified:

3/11/2024

