

Circular conductor terminal large with auxiliary conductor voltage tap
3 units Accessory for: 3VA6 150/250



Model	
Product brand name	SETRON
Product designation	accessories
Design of the product	circular conductor terminal
Connections according IEC	
IEC-marking / of terminals	50-240 mm² CU/AL NNL
Connectable conductor cross-section	
• for copper cable / finely stranded / minimum	50 mm²
• for copper cable / finely stranded / maximum	185 mm²
• for copper cable / stranded / minimum	50 mm²
• for copper cable / stranded / maximum	240 mm²
• for aluminum cable / stranded / minimum	25 mm²
• for aluminum cable / stranded / maximum	240 mm²
Wire stripping length	30,5 mm
Tightening torque / when using copper cables	
• stranded	31 Nm

- finely stranded

31 Nm

Connections according UL

UL-marking / of terminals	TA2.2 CMC 2-350 CU7AL UR CSA
Permissible temperature / of connectable conductor / according to UL 486A-486B	75 °C
Wire stripping length	1.2 in
Connectable conductor cross-section • for copper cable / stranded / minimum • for copper cable / stranded / maximum • for copper cable / finely stranded / minimum • for copper cable / finely stranded / maximum • for aluminum cable / stranded / minimum • for aluminum cable / stranded / maximum	2 AWG 350 kcmil 2 AWG 350 kcmil 2 AWG 350 kcmil
Tightening torque / when using copper cables • stranded • finely stranded	275 lb-in 275 lb-in

Certificates

General Product Approval	EMC	Declaration of Conformity	other
 Miscellaneous			 Miscellaneous

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA9243-0JC13>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VA9243-0JC13>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)






http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA9243-0JC13

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



last modified:

04/10/2018