

circuit breaker VL160X N standard breaking capacity $I_{cu}=55\text{kA}$, 415V AC 3-pole, line protection Electronic Trip Unit TM, LI $I_n=80\text{A}$, rated current $I_r=63\ldots80\text{A}$, overload prot. $I_t=1000\text{A}$, short-circuit prot. without auxiliary release Auxiliary/alarm switch mounting kit 2 AUX (1 NO+1 NC)+1 AS (1 NO)

Model	
type of the driving mechanism / motor drive	No
design of the overcurrent release	TM
General technical data	
number of poles	3
size of the circuit-breaker	3VL1
mechanical service life (switching cycles) / typical	20 000
electrical endurance (switching cycles) / typical	10 000
utilization category	A
performance class for circuit breaker	N
reference code / acc. to DIN 40719 extended according to IEC 204-2 / acc. to IEC 750	Q
operating frequency / maximum	120 1/s
Voltage	
Rated operational voltage U_e / max.	690 V
insulation voltage / rated value	800 V
insulation voltage (U_i) / at AC / rated value	800 V
surge voltage resistance / rated value	8 kV
operating voltage	
rated value / maximum	690 V
for main current circuit / at AC / at 50 Hz / maximum	690 V
for main current circuit / at AC / at 60 Hz / maximum	690 V
for main current circuit / at DC / maximum	500 V
Protection class	
protection class IP	IP20
protection function of the overcurrent release	LI
Current	
operational current	
at 40 °C / rated value	80 A
at 45 °C / rated value	80 A
at 50 °C / rated value	80 A
at 55 °C / rated value	74.4 A
at 60 °C / rated value	74.4 A
at 65 °C / rated value	68.8 A
at 70 °C / rated value	68.8 A
continuous current / rated value	80 A
derating temperature / for the rated value of the continuous current	50 °C
adjustable current response value current	
of the current-dependent overload release / full-scale value	80 A
of instantaneous short-circuit trip unit / minimum	1 000 A
of instantaneous short-circuit trip unit / maximum	1 000 A
Main circuit	
operating frequency	
1 / rated value	50 Hz
2 / rated value	60 Hz

Auxiliary circuit	
number of CO contacts / for auxiliary contacts	0
number of NC contacts / for auxiliary contacts	1
number of NO contacts / for auxiliary contacts	2
Suitability	
suitability for use	system protection
Adjustable parameters	
adjustable current response value current / of the current-dependent overload release / initial value	64 A
Product details	
product component	
• trip indicator	Yes
• auxiliary switch	Yes
• voltage trigger	No
• undervoltage release	No
• undervoltage release with leading contact	No
product extension / optional / motor drive	Yes
Product function	
product function	
• of thermal overload trip unit	adjustable
• grounding protection	No
• for neutral conductors / short-circuit and overload proof	No
• overload protection	Yes
Short circuit	
breaking capacity operating short-circuit current (Ics)	
• at 240 V / rated value	65 kA
• at 415 V / rated value	55 kA
• at 500 V / rated value	14 kA
• at 690 V / rated value	4 kA
breaking capacity maximum short-circuit current (Icu)	
• at 240 V / rated value	65 kA
• at 415 V / rated value	55 kA
• at 440 V / rated value	25 kA
• at 480 V / acc. to NEMA / rated value	25 kA
• at 500 V / rated value	18 kA
• at 600 V / acc. to NEMA / rated value	8 kA
• at 690 V / rated value	8 kA
Connections	
arrangement of electrical connectors / for main current circuit	front side
type of connectable conductor cross-sections / for main contacts	
• with flexible busbar	12 x 10 mm
• solid	2.5 ... 95 mm ²
• finely stranded / with core end processing	2.5 ... 50 mm ²
• stranded	2.5 ... 95 mm ²
type of connectable conductor cross-sections / for auxiliary contacts	
• solid	0.75 ... 1.5 mm ²
• finely stranded / with core end processing	0,75 ... 1.0 mm ²
type of electrical connection / for main current circuit	box terminal
Mechanical Design	
height	157.5 mm
width	104.5 mm
depth	106.5 mm
fastening method	fixed mounting
Environmental conditions	
ambient temperature / during operation	
• minimum	0 °C

• maximum	70 °C
ambient temperature / during storage	
• minimum	-40 °C
• maximum	80 °C
General Product Approval	
EMC	

[Miscellaneous](#)



[TSE](#)

[KC](#)



Declaration of Conformity	Test Certificates	Marine / Shipping			
----------------------------------	--------------------------	--------------------------	--	--	--



[Special Test Certificate](#)



Marine / Shipping	other				
--------------------------	--------------	--	--	--	--



[Environmental Confirmations](#)

[Confirmation](#)

[Miscellaneous](#)

other

[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VL1708-1DD33-0AD1>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VL1708-1DD33-0AD1>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL1708-1DD33-0AD1

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



