



CIRCUIT-BREAKER VL 160N STANDARD BREAKING
CAPACITY ICU=55KA / 415 V AC 3 POLE, LINE
PROTECTION ELECTRONIC TRIP UNIT ETU20, LSI
IN=63A, RATED CURRENT IR=25-63A, OVERLOAD
ISD=1,5TO10XIR, II=11XIN SHORT-CIRCUIT

Certificates

General Product Approval		EMC	Declaration of Conformity
 CCC	sonstig	 EAC	TSE
		 C-TICK	 EG-Konf.

Test Certificates	Shipping Approval				other
spezielle Prüfbescheinigung n	 DNV	 GL	 RINA	 RMRS	Umweltbestätigung

other	
Bestätigungen	sonstig

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3VL27061SE338TD1>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3VL27061SE338TD1/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL27061SE338TD1

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://ausschreibungstexte.siemens.com/tiplv>

last modified:

13.08.2015