

CIRCUIT-BREAKER VL 160H HIGH BREAKING
CAPACITY ICU=70KA / 415 V AC 3 POLE, NON-
AUTOMATIC OVERCURRENT RELEASE MAGNETIC
IN=100A, RATED CURRENT II=2500A, SHORT
CIRCUIT WITH SCREW CONNECTION

Model		
Design of the operating mechanism		toggle handle
Type of the driving mechanism / motor drive		Yes
Design of the overcurrent release		M
General technical data		
Number of poles		3
Size of the circuit-breaker		3VL2
Electrical endurance (switching cycles) / typical		10 000
Usage category		A
Performance class for circuit breaker		N
Mechanical service life (switching cycles) / typical		20 000
Equipment marking / acc. to DIN 40719 extended according to IEC 204-2 / acc. to IEC 750		Q
Operating frequency / maximum	1/s	120
Voltage		
Rated operational voltage Ue / max.	V	690
Insulation voltage		
• rated value	V	800
• at AC / rated value	V	800
Surge voltage resistance / rated value	kV	8
Protection class		
Protection class IP		IP20
Protective function of the overcurrent release		I
Electricity		
Continuous current / rated value	A	100
Derating temperature / for the rated value of the continuous current	°C	50
Adjustable pick-up value current		
• of instantaneous short-circuit trip unit / initial value	A	2 500
• of instantaneous short-circuit trip unit / Full- scale value	A	2 500

Main circuit		
Operating frequency		
• 1 / rated value	Hz	50
• 2 / rated value	Hz	60
Operating voltage		
• for main current circuit / at AC / at 50 Hz / maximum	V	690
• for main current circuit / at AC / at 60 Hz / maximum	V	690
• for main current circuit / at DC / maximum	V	500
Operating current		
• at 40 °C / rated value	A	100
• at 50 °C / rated value	A	100
• at 55 °C / rated value	A	93
• at 60 °C / rated value	A	93
• at 65 °C / rated value	A	86
• at 70 °C / rated value	A	86
Auxiliary circuit		
Number of CO contacts / for auxiliary contacts		0
Number of NC contacts / for auxiliary contacts		1
Number of NO contacts / for auxiliary contacts		2
Suitability		
Suitability for use		non-automatic circuit-breakers
Product details		
Product component		
• Trip indicator		Yes
• Auxiliary switch		Yes
• Voltage trigger		Yes
• undervoltage release		No
• undervoltage release with leading contact		No
Product extension / optional / motor drive		No
Product function		
Product function		
• of thermal overload trip unit		without
• Ground fault protection		No
• for neutral conductors / Short-circuit and overload proof		No
• Overload protection		No
Short circuit		
Operational short-circuit current breaking capacity (Ics)		

• at 240 V / rated value	kA	75
• at 415 V / rated value	kA	70
• at 500 V / rated value	kA	30
• at 690 V / rated value	kA	6
Maximum short-circuit current breaking capacity (Icu)		
• at 240 V / rated value	kA	100
• at 415 V / rated value	kA	70
• at 440 V / rated value	kA	50
• at 480 V / acc. to NEMA / rated value	kA	50
• at 500 V / rated value	kA	40
• at 600 V / acc. to NEMA / rated value	kA	12
• at 690 V / rated value	kA	12

Connections

Arrangement of electrical connectors / for main current circuit		front side
Type of electrical connection / for main current circuit		screw-type terminals

Mechanical Design

Height	mm	174.5
Width	mm	104.5
Depth	mm	106.5
Mounting type		fixed mounting

Environmental conditions

Ambient temperature		
• during operation / minimum	°C	0
• during operation / maximum	°C	70
• during storage / minimum	°C	-40
• during storage / maximum	°C	80

Certificates

Certificate of suitability		IEC, high switching capacity (H)
Equipment marking		
• acc. to DIN EN 61346-2		Q

General Product Approval		EMC	Declaration of Conformity
 CCC	sonstig	 EAC	TSE
		 C-Tick	 EG-Konf.

Test Certificates	Shipping Approval				
spezielle Prüfbescheinigungen	 ABS	 BUREAU VERITAS	 LRS	 PRS	 RINA

Shipping Approval	other				
 RMRS	Umweltbestätigung	Bestätigungen	sonstig		

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3VL2710-2DE36-8QD1-Z L12+M22>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3VL2710-2DE36-8QD1-Z L12+M22/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL2710-2DE36-8QD1-Z L12+M22

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://ausschreibungstexte.siemens.com/tiplv>

last modified:

10/14/2016