

circuit breaker VL160H high breaking capacity Icu=70kA, 415V AC 3-pole, line protection Electronic Trip Unit TM, LI In=160A, rated current IR=125...160A, overload protection, II=800...1600A, short-circuit protection Shunt release 110...127 V DC Auxiliary/alarm switch mounting kit 2 AUX (1 NO+1 NC)+1 AS (1 NO)

Model	
type of the driving mechanism / motor drive	No
design of the overcurrent release	TM
General technical data	
number of poles	3
size of the circuit-breaker	3VL2
mechanical service life (switching cycles) / typical	20 000
electrical endurance (switching cycles) / typical	10 000
utilization category	A
performance class for circuit breaker	N
reference code / according to DIN 40719 extended according to IEC 204-2 / according to IEC 750	Q
operating frequency / maximum	120 1/s
Voltage	
Rated operational voltage Ue / max.	690 V
- insulation voltage / rated value - insulation voltage (Ui) / at AC / rated value	800 V
surge voltage resistance / rated value	8 kV
operating voltage	
- rated value / maximum - for main current circuit / at AC / at 50 Hz / maximum - for main current circuit / at AC / at 60 Hz / maximum - for main current circuit / at DC / maximum	690 V 690 V 690 V 500 V
Protection class	
protection class IP	IP20
protection function of the overcurrent release	LI
Current	
operational current	
- at 40 °C / rated value - at 45 °C / rated value - at 50 °C / rated value - at 55 °C / rated value - at 60 °C / rated value - at 65 °C / rated value - at 70 °C / rated value	160 A 160 A 160 A 148.8 A 148.8 A 137.6 A 137.6 A
continuous current / rated value	160 A
derating temperature / for the rated value of the continuous current	50 °C
adjustable current response value current	
- of the current-dependent overload release / full-scale value - of instantaneous short-circuit trip unit / minimum - of instantaneous short-circuit trip unit / maximum	160 A 800 A 1 600 A
Main circuit	
operating frequency	
1 / rated value 2 / rated value	50 Hz 60 Hz

Auxiliary circuit	
number of CO contacts / for auxiliary contacts	0
number of NC contacts / for auxiliary contacts	1
number of NO contacts / for auxiliary contacts	2
Suitability	
suitability for use	system protection
Adjustable parameters	
adjustable current response value current / of the current-dependent overload release / initial value	128 A
Product details	
product component	
• trip indicator	Yes
• auxiliary switch	Yes
• voltage trigger	Yes
• undervoltage release	No
• undervoltage release with leading contact	No
product extension / optional / motor drive	Yes
Product function	
product function	
• of thermal overload trip unit	adjustable
• grounding protection	No
• for neutral conductors / short-circuit and overload proof	No
• overload protection	Yes
Short circuit	
breaking capacity operating short-circuit current (Ics)	
• at 240 V / rated value	75 kA
• at 415 V / rated value	70 kA
• at 500 V / rated value	30 kA
• at 690 V / rated value	6 kA
breaking capacity maximum short-circuit current (Icu)	
• at 240 V / rated value	100 kA
• at 415 V / rated value	70 kA
• at 440 V / rated value	50 kA
• at 480 V / according to NEMA / rated value	50 kA
• at 500 V / rated value	40 kA
• at 600 V / according to NEMA / rated value	12 kA
• at 690 V / rated value	12 kA
Connections	
arrangement of electrical connectors / for main current circuit	front side
type of connectable conductor cross-sections / for main contacts	
• with flexible busbar	12 x 10 mm
• solid	2.5 ... 95 mm ²
• finely stranded / with core end processing	2.5 ... 50 mm ²
• stranded	2.5 ... 95 mm ²
type of connectable conductor cross-sections / for auxiliary contacts	
• solid	0.75 ... 1.5 mm ²
• finely stranded / with core end processing	0,75 ... 1.0 mm ²
type of electrical connection / for main current circuit	box terminal
Mechanical Design	
height	174.5 mm
width	104.5 mm
depth	106.5 mm
fastening method	fixed mounting
Environmental conditions	
ambient temperature / during operation	
• minimum	0 °C

• maximum	70 °C
ambient temperature / during storage	
• minimum	-40 °C
• maximum	80 °C
General Product Approval	

[Miscellaneous](#)

[Confirmation](#)



[TSE](#)

[KC](#)



EMC	Declaration of Conformity	Test Certificates	Marine / Shipping
C-Tick	EG-Konf.	Special Test Certificate	ABS BUREAU VERITAS

Marine / Shipping	other
LRS PRS RINA RMRS DNV-GL	Miscellaneous

other
Confirmation Environmental Confirmations Miscellaneous

Further information
Information- and Downloadcenter (Catalogs, Brochures,...) http://www.siemens.com/lowvoltage/catalogs Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VL2716-2DC33-8KD1 Service&Support (Manuals, Certificates, Characteristics, FAQs,...) https://support.industry.siemens.com/cs/ww/en/ps/3VL2716-2DC33-8KD1 Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...) http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL2716-2DC33-8KD1 CAX-Online-Generator http://www.siemens.com/cax Tender specifications http://www.siemens.com/specifications



