



CIRCUIT-BREAKER VL 160H HIGH BREAKING
CAPACITY ICU=70KA / 415 V AC 3 POLE, STARTER
COMBINATION PROTECTION OVERCURRENT
RELEASE MAGNETIC IN=160A, RATED CURRENT
II=1250-2500A, SHORT CIRCUIT

Model		
Type of the driving mechanism / motor drive		No
Design of the overcurrent release		M
General technical data		
Number of poles		3
Size of the circuit-breaker		3VL2
Electrical endurance (switching cycles) / typical		10 000
Usage category		A
Performance class for circuit breaker		N
Mechanical service life (switching cycles) / typical		20 000
Equipment marking / acc. to DIN 40719 extended according to IEC 204-2 / acc. to IEC 750		Q
Operating frequency / maximum	1/s	120
Voltage		
Rated operational voltage Ue / max.	V	690
Insulation voltage		
• Rated value	V	800
• at AC / Rated value	V	800

Surge voltage resistance / Rated value	kV	8
Protection class		
Protection class IP		IP20
Protective function of the overcurrent release		I
Electricity		
Continuous current / Rated value	A	160
Derating temperature / for the rated value of the continuous current	°C	50
Adjustable response value current		
• of the instantaneous short-circuit release / initial value	A	1 120
• of the instantaneous short-circuit release / Full-scale value	A	2 400
Main circuit		
Operating frequency		
• 1 / Rated value	Hz	50
• 2 / Rated value	Hz	60
Operating power / at AC-3		
• at 230 V / Rated value	kW	29.4
• at 400 V / Rated value	kW	88.7
Operating voltage		
• for main current circuit / at AC / at 50 Hz / maximum	V	690
• for main current circuit / at AC / at 60 Hz / maximum	V	690
• for main current circuit / at DC / maximum	V	500
Operating current		
• at 40 °C / Rated value	A	160
• at 50 °C / Rated value	A	160
• at 55 °C / Rated value	A	148.8
• at 60 °C / Rated value	A	148.8
• at 65 °C / Rated value	A	137.6
• at 70 °C / Rated value	A	137.6
Auxiliary circuit		
Number of CO contacts / for auxiliary contacts		0
Number of NC contacts / for auxiliary contacts		0
Number of NO contacts / for auxiliary contacts		0
Suitability		
Suitability for use		Starter protection
Product details		
Product component		

• Trip indicator	No
• Auxiliary switch	No
• Voltage trigger	No
• undervoltage release	No
• undervoltage release with leading contact	No
Product expansion / optional / motor drive	Yes

Product function

Product function	
• of the thermal overload release	without
• Ground fault protection	No
• for neutral conductors / Short-circuit and overload proof	No
• overload protection	No

Short circuit

Operational short-circuit current breaking capacity (Ics)	
• at 240 V / Rated value	kA 75
• at 415 V / Rated value	kA 70
• at 500 V / Rated value	kA 30
• at 690 V / Rated value	kA 6
Maximum short-circuit current breaking capacity (Icu)	
• at 240 V / Rated value	kA 100
• at 415 V / Rated value	kA 70
• at 440 V / Rated value	kA 50
• at 480 V / acc. to NEMA / Rated value	kA 50
• at 500 V / Rated value	kA 40
• at 600 V / acc. to NEMA / Rated value	kA 12
• at 690 V / Rated value	kA 12

Connections

Arrangement of electrical connectors / for main current circuit	front side
Type of connectable conductor cross-section	
• for main contacts	
— with flexible busbar	12 x 10 mm
— solid	2.5 ... 95 mm ²
— finely stranded / with core end processing	2.5 ... 50 mm ²
— stranded	2.5 ... 95 mm ²
• for auxiliary contacts	
— solid	0.75 ... 1.5 mm ²
— finely stranded / with core end processing	0,75 ... 1.0 mm ²
Type of electrical connection / for main current circuit	box terminals

Mechanical Design

Height	mm	174.5
Width	mm	104.5
Depth	mm	106.5
Mounting type		fixed mounting

Environmental conditions

Ambient temperature		
• during operation / minimum	°C	0
• during operation / maximum	°C	70
• during storage / minimum	°C	-40
• during storage / maximum	°C	80

Certificates

Certificate of suitability		IEC, high switching capacity (H)
Equipment marking		
• acc. to DIN EN 61346-2		Q

General Product Approval

EMC



[sonstig](#)



[TSE](#)

[KTL](#)



Declaration of Conformity

Test Certificates

Shipping Approval



EG-Konf.

[spezielle
Prüfbescheinigunge
n](#)



ABS



BUREAU
VERITAS



DNV



GL

Shipping Approval

other



LRS



PRS



RINA



RMRS

[Bestätigungen](#)

[Umweltbestätigung](#)

other

[sonstig](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3VL27162DK330AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3VL27162DK330AA0/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL27162DK330AA0

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://ausschreibungstexte.siemens.com/tiplv>

last modified:

11.09.2015