

CIRCUIT-BREAKER VL 250 UL; TYPE FG (CAT NO. LFX3B250)
 NON-INTERCHANGEABLE FRAME W. APPROBATION CIRCUIT-
 BREAKER TO UL489 VERY HIGH BREAKING CAPACITY 3-POLE,
 NEMA RATING 100KA/480V, (MOLDED CASE CIRCUIT BREAKER)
 OVERCURRENT RELEASE TM, LI TU= 40 DEGR. CELSIUS IN= <
 250A, RATED CURRENT II= 1250...2500A SHORT-CIRCUIT
 PROTECTION IR= 250A OVERCURRENT RELEASE F. PLANT
 PROTECTION W/O CONNECTION ACCESSORIES

Model	
Type of the driving mechanism / motor drive	No
Design of the overcurrent release	TM
General technical data	
Number of poles	3
Size of the circuit-breaker	3VL3 UL
Electrical endurance (switching cycles) / typical	10 000
Usage category	A
Performance class for circuit breaker	N
Mechanical service life (switching cycles) / typical	20 000
Equipment marking / acc. to DIN 40719 extended according to IEC 204-2 / acc. to IEC 750	Q
Operating frequency / maximum	120 1/s
Voltage	
Rated operational voltage Ue / max.	690 V
Insulation voltage	
• rated value	800 V
• at AC / rated value	800 V

Surge voltage resistance / rated value	8 kV
Protection class	
Protection class IP	IP20
Protective function of the overcurrent release	LI
Dissipation	
Power loss [W]	
• maximum	80 W
Electricity	
Continuous current / rated value	250 A
Derating temperature / for the rated value of the continuous current	
• acc. to UL 489	40 °C
Adjustable pick-up value current	
• of the current-dependent overload release / Full-scale value	250 A
• of instantaneous short-circuit trip unit / initial value	1 250 A
• of instantaneous short-circuit trip unit / Full-scale value	2 500 A
Main circuit	
Operating frequency	
• 1 / rated value	50 Hz
• 2 / rated value	60 Hz
Operating voltage	
• for main current circuit / at AC / at 50 Hz / acc. to UL 489 / maximum	600 V
• for main current circuit / at AC / at 50 Hz / maximum	690 V
• for main current circuit / at AC / at 60 Hz / acc. to UL 489 / maximum	600 V
• for main current circuit / at AC / at 60 Hz / maximum	690 V
• for main current circuit / at DC / acc. to UL 489 / maximum	500 V
Operating current	
• at 40 °C / rated value	250 A
• at 50 °C / rated value	232.5 A
• at 55 °C / rated value	215 A
• at 60 °C / rated value	215 A
Suitability	
Suitability for use	system protection

Adjustable parameters

Adjustable pick-up value current / of the current-dependent overload release / initial value	250 A
---	-------

Product details

Product component

• Trip indicator	No
• Auxiliary switch	Yes
• Voltage trigger	No
• undervoltage release	No
• undervoltage release with leading contact	No

Product extension / optional / motor drive	Yes
--	-----

Product function

Product function

• of thermal overload trip unit	fixed
• Ground fault protection	No
• for neutral conductors / Short-circuit and overload proof	No
• Overload protection	Yes

Short circuit

Operational short-circuit current breaking capacity (Ics)

• at 240 V / rated value	150 kA
• at 415 V / rated value	75 kA
• at 690 V / rated value	6 kA

Maximum short-circuit current breaking capacity (Icu)

• at 240 V / rated value	200 kA
• at 415 V / rated value	100 kA
• at 480 V / acc. to NEMA / rated value	100 kA
• at 600 V / acc. to NEMA / rated value	25 kA
• at 690 V / rated value	12 kA

Connections

Arrangement of electrical connectors / for main current circuit	front side
Type of electrical connection / for main current circuit	without connection accessoires

Mechanical Design

Height	185.5 mm
Width	104.5 mm
Depth	106.5 mm
Mounting type	fixed mounting

Environmental conditions

Ambient temperature	
• during operation / minimum	0 °C
• during operation / maximum	70 °C
• during storage / minimum	-40 °C
• during storage / maximum	80 °C

Certificates	
Certificate of suitability	UL very high switching capacity (L), non-interchangeable
Equipment marking	Q

General Product Approval	EMC	Declaration of Conformity	Test Certificates
 CCC	 C-Tick	 EG-Konf.	spezielle Prüfbescheinigungen n

Shipping Approval	other
 RMRS	sonstig Umweltbestätigung Bestätigungen

Further information
Information- and Downloadcenter (Catalogs, Brochures,...) http://www.siemens.com/lowvoltage/catalogs
Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VL3125-3KN30-0AB1
Service&Support (Manuals, Certificates, Characteristics, FAQs,...) http://support.automation.siemens.com/WW/view/en/3VL3125-3KN30-0AB1/all
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...) http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL3125-3KN30-0AB1
CAX-Online-Generator http://www.siemens.com/cax
Tender specifications http://www.siemens.com/specifications