




CIRCUIT-BREAKER VL 250 UL TYPE FG (CAT NO. NFK3B175)
NON-INTERCHANGEABLE FRAME W. APPROBATION CIRCUIT-
BREAKER ACC. UL489 STANDARD BREAKING CAPACITY 3-
POLE, NEMA RATING 35KA@480V AND 18KA@600/347V
(MOLDED CASE CIRCUIT BREAKER) OVERCURRENT RELEASE
TM, LI TU= 40 DEGR. CELSIUS IN=175A, RATED CURRENT II=
1000...2000A SHORT-CIRCUIT PROTECTION IR= 175A
OVERCURRENT RELEASE F. PLANT PROTECTION W/O
CONNECTION ACCESSORIES

Model	
Type of the driving mechanism / motor drive	No
Design of the overcurrent release	TM
General technical data	
Number of poles	3
Size of the circuit-breaker	3VL3 UL
Electrical endurance (switching cycles) / typical	10 000
Usage category	A
Performance class for circuit breaker	N
Mechanical service life (switching cycles) / typical	20 000
Equipment marking / acc. to DIN 40719 extended according to IEC 204-2 / acc. to IEC 750	Q
Operating frequency / maximum	120 1/s
Voltage	
Rated operational voltage Ue / max.	690 V
Insulation voltage	
• rated value	800 V
• at AC / rated value	800 V

Surge voltage resistance / rated value	8 kV
Protection class	
Protection class IP	IP20
Protective function of the overcurrent release	LI
Electricity	
Operating current / at 45 °C / rated value	162.8 A
Continuous current / rated value	175 A
Derating temperature / for the rated value of the continuous current	50 °C
• acc. to UL 489	40 °C
Adjustable pick-up value current	
• of the current-dependent overload release / Full-scale value	175 A
• of instantaneous short-circuit trip unit / initial value	1 000 A
• of instantaneous short-circuit trip unit / Full-scale value	2 000 A
Main circuit	
Operating frequency	
• 1 / rated value	50 Hz
• 2 / rated value	60 Hz
Operating voltage	
• rated value / maximum	690 V
• for main current circuit / at AC / at 50 Hz / acc. to UL 489 / maximum	600 V
• for main current circuit / at AC / at 50 Hz / maximum	690 V
• for main current circuit / at AC / at 60 Hz / acc. to UL 489 / maximum	600 V
• for main current circuit / at AC / at 60 Hz / maximum	690 V
Operating current	
• at 40 °C / rated value	175 A
• at 50 °C / rated value	162.8 A
• at 55 °C / rated value	150.5 A
• at 60 °C / rated value	150.5 A
Suitability	
Suitability for use	system protection
Adjustable parameters	
Adjustable pick-up value current / of the current-dependent overload release / initial value	175 A

Product details

Product component

• Trip indicator	No
• Auxiliary switch	No
• Voltage trigger	No
• undervoltage release	No
• undervoltage release with leading contact	No

Product extension / optional / motor drive	Yes
--	-----

Product function

Product function

• of thermal overload trip unit	fixed
• Ground fault protection	No
• for neutral conductors / Short-circuit and overload proof	No
• Overload protection	Yes

Short circuit

Operational short-circuit current breaking capacity (Ics)

• at 240 V / rated value	65 kA
--------------------------	-------

Maximum short-circuit current breaking capacity (Icu)

• at 240 V / rated value	65 kA
• at 480 V / acc. to NEMA / rated value	35 kA

Connections

Arrangement of electrical connectors / for main current circuit	front side
---	------------

Type of electrical connection / for main current circuit	without connection accessoires
--	--------------------------------

Mechanical Design

Height	185.5 mm
Width	104.5 mm
Depth	106.5 mm
Mounting type	fixed mounting

Environmental conditions

Ambient temperature

• during operation / minimum	0 °C
• during operation / maximum	70 °C
• during storage / minimum	-40 °C
• during storage / maximum	80 °C

Certificates

Certificate of suitability	UL standard switching capacity (N), non-interchangeable
----------------------------	---

Equipment marking

General Product Approval	EMC	Declaration of Conformity
--------------------------	-----	---------------------------



CCC



CSA

[Miscellaneous](#)



UL



C-Tick



EG-Konf.

Test Certificates	Shipping Approval	other
-------------------	-------------------	-------

[Special Test Certificate](#)



RMRS

[Miscellaneous](#)

[Environmental Confirmations](#)

[Confirmation](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VL3517-1KN30-0AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VL3517-1KN30-0AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL3517-1KN30-0AA0

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>