




CIRCUIT-BREAKER VL 250H HIGH BREAKING
CAPACITY ICU=70KA / 415 V AC 3 POLE, STARTER
COMBINATION PROTECTION OVERCURRENT
RELEASE MAGNETIC IN=250A, RATED CURRENT
II=1750-3500A, SHORT-CIRCUIT

Model		
Type of the driving mechanism / motor drive		No
Design of the overcurrent release		M
General technical data		
Number of poles		3
Size of the circuit-breaker		3VL3
Electrical endurance (switching cycles) / typical		10 000
Usage category		A
Performance class for circuit breaker		N
Mechanical service life (switching cycles) / typical		20 000
Equipment marking / acc. to DIN 40719 extended according to IEC 204-2 / acc. to IEC 750		Q
Operating frequency / maximum	1/s	120
Voltage		
Rated operational voltage Ue / max.	V	690
Insulation voltage		
• rated value	V	800
• at AC / rated value	V	800

Surge voltage resistance / rated value	kV	8
Protection class		
Protection class IP		IP20
Protective function of the overcurrent release		I
Dissipation		
Power loss [W]		
• maximum	W	60
Electricity		
Continuous current / rated value	A	250
Derating temperature / for the rated value of the continuous current	°C	50
Adjustable pick-up value current		
• of instantaneous short-circuit trip unit / initial value	A	1 750
• of instantaneous short-circuit trip unit / Full-scale value	A	3 750
Main circuit		
Operating frequency		
• 1 / rated value	Hz	50
• 2 / rated value	Hz	60
Operating power / at AC-3		
• at 230 V / rated value	kW	46
• at 400 V / rated value	kW	138.5
Operating voltage		
• for main current circuit / at AC / at 50 Hz / maximum	V	690
• for main current circuit / at AC / at 60 Hz / maximum	V	690
• for main current circuit / at DC / maximum	V	500
Operating current		
• at 40 °C / rated value	A	250
• at 50 °C / rated value	A	250
• at 55 °C / rated value	A	232.5
• at 60 °C / rated value	A	232.5
• at 65 °C / rated value	A	215
• at 70 °C / rated value	A	215
Suitability		
Suitability for use		Starter protection
Product details		
Product component		
• Trip indicator		No

• Auxiliary switch		Yes
• Voltage trigger		No
• undervoltage release		No
• undervoltage release with leading contact		No
Product extension / optional / motor drive		Yes

Product function

Product function		
• of thermal overload trip unit		without
• Ground fault protection		No
• for neutral conductors / Short-circuit and overload proof		No
• Overload protection		No

Short circuit

Operational short-circuit current breaking capacity (Ics)		
• at 240 V / rated value	kA	75
• at 415 V / rated value	kA	70
• at 500 V / rated value	kA	30
• at 690 V / rated value	kA	6
Maximum short-circuit current breaking capacity (Icu)		
• at 240 V / rated value	kA	100
• at 415 V / rated value	kA	70
• at 440 V / rated value	kA	50
• at 480 V / acc. to NEMA / rated value	kA	50
• at 500 V / rated value	kA	40
• at 600 V / acc. to NEMA / rated value	kA	12
• at 690 V / rated value	kA	12

Connections

Arrangement of electrical connectors / for main current circuit		front side
Type of electrical connection / for main current circuit		screw-type terminals

Mechanical Design

Height	mm	185.5
Width	mm	104.5
Depth	mm	106.5
Mounting type		fixed mounting

Environmental conditions

Ambient temperature		
• during operation / minimum	°C	0
• during operation / maximum	°C	70

- during storage / minimum
- during storage / maximum

°C	-40
°C	80

Certificates

Certificate of suitability	IEC, high switching capacity (H)
Equipment marking	Q
• acc. to DIN EN 61346-2	

General Product Approval	EMC
 CCC	 EAC
 C-Tick	

[sonstig](#)

[TSE](#)

[KTL](#)

Declaration of Conformity	Test Certificates	Shipping Approval
 EG-Konf.	spezielle Prüfbescheinigung n	 ABS
		 BUREAU VERITAS
		 LRS
		 PRS

Shipping Approval	other
 RINA	Umweltbestätigung Bestätigungen sonstig
 RMRS	

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3VL3725-2DK36-0AB1>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3VL3725-2DK36-0AB1/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL3725-2DK36-0AB1

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://ausschreibungstexte.siemens.com/tiplv>