



CIRCUIT-BREAKER VL 400N STANDARD BREAKING CAPACITY ICU=55KA / 415 V AC 3 POLE, MOTOR/ GENERATOR PROTECTION ELECTRONIC TRIP UNIT ETU10M, LI IN=315A, RATED CURRENT IR=125-315A, OVERLOAD II=1,25TO11XIN, SHORT CIRCUIT

Model		
Type of the driving mechanism / motor drive		No
Design of the overcurrent release		ETU10M
General technical data		
Number of poles		3
Size of the circuit-breaker		3VL4
Electrical endurance (switching cycles) / typical		10 000
Usage category		A
Performance class for circuit breaker		N
Mechanical service life (switching cycles) / typical		20 000
Equipment marking / acc. to DIN 40719 extended according to IEC 204-2 / acc. to IEC 750		Q
Operating frequency / maximum	1/s	120
Voltage		
Rated operational voltage Ue / max.	V	690
Insulation voltage		
• rated value	V	800
• at AC / rated value	V	800

Surge voltage resistance / rated value	kV	8
Protection class		
Protection class IP		IP20
Protective function of the overcurrent release		LI
Dissipation		
Power loss [W]		
• maximum	W	60
Electricity		
Continuous current / rated value	A	315
Derating temperature / for the rated value of the continuous current	°C	50
Adjustable response value current		
• of the current-dependent overload release / Full-scale value	A	315
• of the instantaneous short-circuit release / initial value	A	394
• of the instantaneous short-circuit release / Full-scale value	A	3 465
Main circuit		
Operating frequency		
• 1 / rated value	Hz	50
• 2 / rated value	Hz	60
Operating power / at AC-3		
• at 230 V / rated value	kW	57.9
• at 400 V / rated value	kW	174.6
Operating voltage		
• for main current circuit / at AC / at 50 Hz / maximum	V	690
• for main current circuit / at AC / at 60 Hz / maximum	V	690
• for main current circuit / at DC / maximum	V	500
Operating current		
• at 40 °C / rated value	A	315
• at 50 °C / rated value	A	315
• at 55 °C / rated value	A	299.3
• at 60 °C / rated value	A	299.3
• at 65 °C / rated value	A	252
• at 70 °C / rated value	A	252
Auxiliary circuit		
Number of CO contacts / for auxiliary contacts		0
Number of NC contacts / for auxiliary contacts		0

Number of NO contacts / for auxiliary contacts		0
Suitability		
Suitability for use		Motor Protection
Adjustable parameters		
Adjustable response value current / of the current-dependent overload release / initial value	A	126
Product details		
Product component		
• Trip indicator		No
• Auxiliary switch		No
• Voltage trigger		No
• undervoltage release		No
• undervoltage release with leading contact		No
Product expansion / optional / motor drive		Yes
Product function		
Product function		
• of the thermal overload release		adjustable
• Ground fault protection		No
• for neutral conductors / Short-circuit and overload proof		No
• Overload protection		Yes
Short circuit		
Operational short-circuit current breaking capacity (Ics)		
• at 240 V / rated value	kA	65
• at 415 V / rated value	kA	55
• at 500 V / rated value	kA	20
• at 690 V / rated value	kA	8
Maximum short-circuit current breaking capacity (Icu)		
• at 240 V / rated value	kA	65
• at 415 V / rated value	kA	55
• at 440 V / rated value	kA	35
• at 480 V / acc. to NEMA / rated value	kA	35
• at 500 V / rated value	kA	25
• at 600 V / acc. to NEMA / rated value	kA	20
• at 690 V / rated value	kA	15
Connections		
Arrangement of electrical connectors / for main current circuit		front side
Type of connectable conductor cross-sections		

• for main contacts — with flexible busbar — solid — finely stranded / with core end processing — stranded • for auxiliary contacts — solid — finely stranded / with core end processing		25 x 10 50 ... 300 mm ² 50 ... 240 mm ² 50 ... 300 mm ² 0.75 ... 1.5 mm ² 0,75 ... 1.0 mm ²
Type of electrical connection / for main current circuit		screw-type terminals

Mechanical Design

Height	mm	279.5
Width	mm	139
Depth	mm	163.5
Mounting type		fixed mounting

Environmental conditions

Ambient temperature		
• during operation / minimum • during operation / maximum • during storage / minimum • during storage / maximum	°C °C °C °C	-25 70 -40 80

Certificates

Certificate of suitability		IEC, standard switching capacity (N)
Equipment marking		
• acc. to DIN EN 61346-2		Q

General Product Approval				EMC	Declaration of Conformity
 CCC	 CSA	sonstig	 EAC	 C-TICK	 EG-Konf.

Test Certificates	Shipping Approval				other
spezielle Prüfbescheinigung n	 DNV	 GL	 RINA	 RMRS	sonstig

other	
Bestätigungen	Umweltbestätigung

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3VL47311SP360AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3VL47311SP360AA0/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL47311SP360AA0

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://ausschreibungstexte.siemens.com/tiplv>

last modified:

11.12.2015