




CIRCUIT-BREAKER VL 400H HIGH BREAKING
CAPACITY ICU=70KA / 415 V AC 3 POLE, STARTER
COMBINATION PROTECTION OVERCURRENT
RELEASE MAGNETIC IN=315A, RATED CURRENT
II=2000-4000A, SHORT-CIRCUIT

Model		
Type of the driving mechanism / motor drive		No
Design of the overcurrent release		M
General technical data		
Number of poles		3
Tripping characteristics / Upper tolerance band		AK_VL250_TM_LIN_u.txt
Tripping characteristics / Lower tolerance band		AK_VL800_TM_I_o.txt
Size of the circuit-breaker		3VL4
Electrical endurance (switching cycles) / typical		10 000
Usage category		A
Performance class for circuit breaker		N
Mechanical service life (switching cycles) / typical		20 000
Equipment marking / acc. to DIN 40719 extended according to IEC 204-2 / acc. to IEC 750		Q
Operating frequency / maximum	1/s	120
Voltage		
Rated operational voltage Ue / max.	V	690
Insulation voltage		

• Rated value	V	800
• at AC / Rated value	V	800
Surge voltage resistance / Rated value	kV	8

Protection class

Protection class IP		IP20
Protective function of the overcurrent release		I

Electricity

Continuous current / Rated value	A	315
Derating temperature / for the rated value of the continuous current	°C	50
Adjustable response value current		
• of the instantaneous short-circuit release / initial value	A	2 205
• of the instantaneous short-circuit release / Full-scale value	A	4 725

Main circuit

Operating frequency		
• 1 / Rated value	Hz	50
• 2 / Rated value	Hz	60
Operating power / at AC-3		
• at 230 V / Rated value	kW	57.9
• at 400 V / Rated value	kW	174.6
Operating voltage		
• for main current circuit / at AC / at 50 Hz / maximum	V	690
• for main current circuit / at AC / at 60 Hz / maximum	V	690
• for main current circuit / at DC / maximum	V	500
Operating current		
• at 40 °C / Rated value	A	315
• at 50 °C / Rated value	A	315
• at 55 °C / Rated value	A	293
• at 60 °C / Rated value	A	293
• at 65 °C / Rated value	A	270.9
• at 70 °C / Rated value	A	270.9

Auxiliary circuit

Number of CO contacts / for auxiliary contacts		0
Number of NC contacts / for auxiliary contacts		1
Number of NO contacts / for auxiliary contacts		1

Suitability

Suitability for use		Starter protection
----------------------------	--	--------------------

Product details

Product component		
• Trip indicator		No
• Auxiliary switch		Yes
• Voltage trigger		No
• undervoltage release		No
• undervoltage release with leading contact		No
Product expansion / optional / motor drive		Yes

Product function

Product function		
• of the thermal overload release		without
• Ground fault protection		No
• for neutral conductors / Short-circuit and overload proof		No
• overload protection		No

Short circuit

Operational short-circuit current breaking capacity (Ics)		
• at 240 V / Rated value	kA	75
• at 415 V / Rated value	kA	70
• at 500 V / Rated value	kA	30
• at 690 V / Rated value	kA	8
Maximum short-circuit current breaking capacity (Icu)		
• at 240 V / Rated value	kA	100
• at 415 V / Rated value	kA	70
• at 440 V / Rated value	kA	50
• at 480 V / acc. to NEMA / Rated value	kA	50
• at 500 V / Rated value	kA	40
• at 600 V / acc. to NEMA / Rated value	kA	20
• at 690 V / Rated value	kA	15

Connections

Arrangement of electrical connectors / for main current circuit		front side
Type of connectable conductor cross-section		
• for main contacts		
— with flexible busbar		25 x 10
— solid		50 ... 300 mm ²
— finely stranded / with core end processing		50 ... 240 mm ²
— stranded		50 ... 300 mm ²
• for auxiliary contacts		
— solid		0.75 ... 1.5 mm ²

— finely stranded / with core end processing		0,75 ... 1.0 mm ²
Type of electrical connection / for main current circuit		screw-type terminals

Mechanical Design		
Height	mm	279.5
Width	mm	139
Depth	mm	163.5
Mounting type		fixed mounting

Environmental conditions		
Ambient temperature		
• during operation / minimum	°C	0
• during operation / maximum	°C	70
• during storage / minimum	°C	-40
• during storage / maximum	°C	80

Certificates		
Certificate of suitability		IEC, high switching capacity (H)
Equipment marking		
• acc. to DIN EN 61346-2		Q

General Product Approval		EMC
 CCC	 CSA	 EAC

[sonstig](#)

[KTL](#)



Declaration of Conformity	Test Certificates	Shipping Approval			
 EG-Konf.	spezielle Prüfbescheinigung n	 BUREAU VERITAS	 DNV	 GL	 LRS

Shipping Approval			other		
 PRS	 RINA	 RMRS	Umweltbestätigung	Bestätigungen	sonstig

Further information	
Information- and Downloadcenter (Catalogs, Brochures,...) http://www.siemens.com/lowvoltage/catalogs	
Industry Mall (Online ordering system) https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3VL47312DK360AB1	

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3VL47312DK360AB1/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL47312DK360AB1

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://ausschreibungstexte.siemens.com/tiplv>

last modified:

13.08.2015