




Similar to image

CIRCUIT-BREAKER VL 630N STANDARD BREAKING
CAPACITY ICU=55KA / 415 V AC 3 POLE,
STARTER COMBINATION PROTECTION OVERCURRENT
RELEASE MAGNETIC IN=500A,
RATED CURRENT II=3250-6300A,
SHORT CIRCUIT WITHOUT AUXILIARY RELEASE
AUXILIARY SWITCH KIT 4HS(2NO+2NC)

General technical data:

Number of poles		3
Design of the overcurrent release		M
Acceptability for application		Starter protection
Electrical operating cycles as operating time / typical		5,000
Mechanical operating cycles as operating time / typical		10,000
Active power loss / maximum	W	160
Product component		
• auxiliary switch		Yes
• Voltage trigger		No
• undervoltage release mechanism		No
• undervoltage release with leading contact		No
Product function		
• ground-fault protection		No
• for zero conductors / short-circuit and overload protection		No
• overload protection		No
Operating cycles / maximum	1/s	60
Protection class IP		IP20
Protective function of the overcurrent release		I

Impulse voltage resistance / rated value	kV	8
Ambient temperature		
• during operating	°C	0 ... 70
• during storage	°C	-40 ... +80

Main circuit:

Insulation voltage / for AC / rated value	V	800
Operating frequency		
• 1 / rated value	Hz	50
• 2 / rated value	Hz	60
Service power / at AC-3		
• at 230 V / rated value	kW	92
• at 400 V / rated value	kW	277.1
Reference code		
• according to DIN 40719 extended according to IEC 204-2 / according to IEC 750		Q
• according to DIN EN 61346-2		Q
Operating voltage / for main circuit		
• at 50 Hz / with AC		
• maximum	V	690
• at 60 Hz / with AC		
• maximum	V	690
Operating voltage / for main current circuit / for DC		
• maximum	V	500
Operating current		
• at 40 °C / rated value	A	500
• at 50 °C / rated value	A	500
• at 60 °C / rated value	A	465
• at 70 °C / rated value	A	430
Continuous current / rated value	A	500
Derating temperature / for the rated value of the continuous current	°C	50

Auxiliary circuit:

Number of NC contacts / for auxiliary contacts		2
Number of NO contacts / for auxiliary contacts		2

Short-circuit:

Adjustable response current		
• of the non-delayed short-circuit release	A	3,500 ... 7,500
Breaking capacity limit short-circuit current (I_{cu}) / at 415 V / rated value	kA	55

Installation/mounting/dimensions:

Mounting type		fixed mounting
Height	mm	279.5
Width	mm	190
Depth	mm	138.5

Connections:

Arrangement of electrical connectors / for main current circuit		front side
Design of the electrical connection / for main current circuit		screw-type terminals
Type of the connectable conductor cross-section • for auxiliary contacts • solid • finely stranded / with conductor end processing		0.75 ... 1.5 mm ² 0,75 ... 1.0 mm ²

Certificates/approvals:

General Product Approval



CCC

[TSE](#)

Declaration of Conformity



EG-Konf.

Test Certificates

[Special Test Certificate](#)

Shipping Approval



BUREAU
VERITAS



DNV



GL



PRS



RINA



RMRS

other

[Confirmation](#)

[other](#)

[Environmental
Confirmations](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3VL5750-1DK36-0AC1>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3VL5750-1DK36-0AC1/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL5750-1DK36-0AC1

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

[Datanorm](#) [GAEB81](#) [GAEB83](#) [RTF](#) [TXT](#)

last change:

Jun 16, 2014