

CIRCUIT-BREAKER VL 630H HIGH BREAKING
CAPACITY ICU=70KA / 415 V AC 3 POLE, LINE
PROTECTION ELECTRONIC TRIP UNIT ETU10, LI
IN=630A, RATED CURRENT IR=252-630A,
OVERLOAD II=1,25TO10XIN, SHORT CIRCUIT

Model		
Type of the driving mechanism / motor drive		No
Design of the overcurrent release		ETU10
General technical data		
Number of poles		3
Size of the circuit-breaker		3VL5
Electrical endurance (switching cycles) / typical		5 000
Usage category		A
Performance class for circuit breaker		N
Mechanical service life (switching cycles) / typical		10 000
Equipment marking / acc. to DIN 40719 extended according to IEC 204-2 / acc. to IEC 750		Q
Operating frequency / maximum	1/s	60
Voltage		
Rated operational voltage Ue / max.	V	690
Insulation voltage		
• Rated value	V	800
• at AC / Rated value	V	800
Surge voltage resistance / Rated value	kV	8
Protection class		
Protection class IP		IP20
Protective function of the overcurrent release		LI
Dissipation		
Active power loss		
• maximum	W	160
Electricity		
Continuous current / Rated value	A	630
Derating temperature / for the rated value of the continuous current	°C	50
Adjustable response value current		
• of the current-dependent overload release / Full-scale value	A	630

- of the instantaneous short-circuit release / initial value
- of the instantaneous short-circuit release / Full-scale value

A	788
A	6 300

Main circuit

Operating frequency

- 1 / Rated value
- 2 / Rated value

Hz	50
Hz	60

Operating voltage

- for main current circuit / at AC / at 50 Hz / maximum
- for main current circuit / at AC / at 60 Hz / maximum

V	690
V	690

Operating current

- at 40 °C / Rated value
- at 50 °C / Rated value
- at 55 °C / Rated value
- at 60 °C / Rated value
- at 65 °C / Rated value
- at 70 °C / Rated value

A	630
A	630
A	598.5
A	598.5
A	504
A	504

Auxiliary circuit

Number of CO contacts / for auxiliary contacts

0

Number of NC contacts / for auxiliary contacts

1

Number of NO contacts / for auxiliary contacts

2

Suitability

Suitability for use

system protection

Adjustable parameters

Adjustable response value current / of the current-dependent overload release / initial value

A 252

Product details

Product component

- Trip indicator
- Auxiliary switch
- Voltage trigger
- undervoltage release
- undervoltage release with leading contact

Yes
Yes
Yes
No
No

Product expansion / optional / motor drive

Yes

Product function

Product function

- of the thermal overload release

adjustable

- Ground fault protection
- for neutral conductors / Short-circuit and overload proof
- overload protection

No
No
Yes

Short circuit

Operational short-circuit current breaking capacity (Ics)

- at 240 V / Rated value
- at 415 V / Rated value
- at 500 V / Rated value
- at 690 V / Rated value

kA 75
kA 70
kA 30
kA 10

Maximum short-circuit current breaking capacity (Icu)

- at 240 V / Rated value
- at 415 V / Rated value
- at 440 V / Rated value
- at 480 V / acc. to NEMA / Rated value
- at 500 V / Rated value
- at 600 V / acc. to NEMA / Rated value
- at 690 V / Rated value

kA 100
kA 70
kA 50
kA 50
kA 40
kA 30
kA 20

Connections

Arrangement of electrical connectors / for main current circuit

front side

Type of connectable conductor cross-section

- for auxiliary contacts
 - solid
 - finely stranded / with core end processing

0.75 ... 1.5 mm²
0,75 ... 1.0 mm²

Type of electrical connection / for main current circuit

screw-type terminals

Mechanical Design

Height

mm 279.5

Width

mm 190

Depth

mm 138.5

Mounting type

fixed mounting

Environmental conditions

Ambient temperature

- during operation / minimum
- during operation / maximum
- during storage / minimum
- during storage / maximum

°C -25
°C 70
°C -40
°C 80

Certificates

Certificate of suitability

IEC, high switching capacity (H)

Equipment marking

- acc. to DIN EN 61346-2

Q

General Product Approval

EMC

Declaration of Conformity



CCC

[sonstig](#)



[TSE](#)



C-TICK



EG-Konf.

Test Certificates

Shipping Approval

other

[spezielle](#)

[Prüfbescheinigung](#)

[n](#)



DNV



GL



RINA



RMRS

[sonstig](#)

other

[Umweltbestätigung](#)

[Bestätigungen](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3VL57632SB368QE1>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3VL57632SB368QE1/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL57632SB368QE1

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://ausschreibungstexte.siemens.com/tiplv>

last modified:

23.10.2015