

circuit breaker VL630H high breaking capacity Icu=70kA, 415V AC 3-pole, line protection trip unit ETU12, LIG 3 phases/3 lines In=630A, rated current IR=252...630A, overload protection, II=1.25 to 10xIN, short-circuit protection without auxiliary release without auxiliary/alarm switch

Model	
type of the driving mechanism / motor drive	No
design of the overcurrent release	ETU12
General technical data	
number of poles	3
size of the circuit-breaker	3VL5
mechanical service life (switching cycles) / typical	10 000
electrical endurance (switching cycles) / typical	5 000
utilization category	A
performance class for circuit breaker	N
reference code / according to DIN 40719 extended according to IEC 204-2 / according to IEC 750	Q
operating frequency / maximum	60 1/s
Voltage	
Rated operational voltage Ue / max.	690 V
- insulation voltage / rated value - insulation voltage (Ui) / at AC / rated value	800 V
surge voltage resistance / rated value	8 kV
operating voltage - rated value / maximum - for main current circuit / at AC / at 50 Hz / maximum - for main current circuit / at AC / at 60 Hz / maximum	690 V
Protection class	
protection class IP	IP20
protection function of the overcurrent release	LIG
Current	
operational current - at 40 °C / rated value - at 45 °C / rated value - at 50 °C / rated value - at 55 °C / rated value - at 60 °C / rated value - at 65 °C / rated value - at 70 °C / rated value	630 A
continuous current / rated value	630 A
derating temperature / for the rated value of the continuous current	50 °C
adjustable current response value current - of the current-dependent overload release / full-scale value - of instantaneous short-circuit trip unit / minimum - of instantaneous short-circuit trip unit / maximum	630 A
Main circuit	
operating frequency 1 / rated value 2 / rated value	50 Hz
Auxiliary circuit	
number of CO contacts / for auxiliary contacts	0

number of NC contacts / for auxiliary contacts	0
number of NO contacts / for auxiliary contacts	0
Suitability	
suitability for use	system protection
Adjustable parameters	
adjustable current response value current / of the current-dependent overload release / initial value	252 A
Product details	
product component	
• trip indicator	No
• auxiliary switch	No
• voltage trigger	No
• undervoltage release	No
• undervoltage release with leading contact	No
product extension / optional / motor drive	Yes
Product function	
product function	
• of thermal overload trip unit	adjustable
• grounding protection	Yes
• for neutral conductors / short-circuit and overload proof	No
• overload protection	Yes
Short circuit	
breaking capacity operating short-circuit current (Ics)	
• at 240 V / rated value	75 kA
• at 415 V / rated value	70 kA
• at 500 V / rated value	30 kA
• at 690 V / rated value	10 kA
breaking capacity maximum short-circuit current (Icu)	
• at 240 V / rated value	100 kA
• at 415 V / rated value	70 kA
• at 440 V / rated value	50 kA
• at 480 V / according to NEMA / rated value	50 kA
• at 500 V / rated value	40 kA
• at 600 V / according to NEMA / rated value	30 kA
• at 690 V / rated value	20 kA
Connections	
arrangement of electrical connectors / for main current circuit	front side
type of connectable conductor cross-sections / for auxiliary contacts	
• solid	0.75 ... 1.5 mm ²
• finely stranded / with core end processing	0,75 ... 1.0 mm ²
type of electrical connection / for main current circuit	screw-type terminals
Mechanical Design	
height	279.5 mm
width	190 mm
depth	138.5 mm
fastening method	fixed mounting
Environmental conditions	
ambient temperature / during operation	
• minimum	-25 °C
• maximum	70 °C
ambient temperature / during storage	
• minimum	-40 °C
• maximum	80 °C
General Product Approval	
EMC	

[Confirmation](#)[Miscellaneous](#)[TSE](#)

Declaration of Conformity

Test Certificates

Marine / Shipping

[UK Declaration of Conformity](#)[Special Test Certificate](#)

other

[Environmental Conformations](#)[Miscellaneous](#)[Confirmation](#)[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VL5763-2SL36-0AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VL5763-2SL36-0AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL5763-2SL36-0AA0

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



