

WITHDRAWABLE CIRCUIT BREAKER WITH GUIDE
FRAME 4-POLE, SIZE I, IEC IN=630A TO 690V,
AC50/60HZ ICU=55KA AT 500V REAR CONNECTION
HORIZONTAL

Model		
product brandname		SETRON
Product designation		ACB
Design of the operating mechanism		Pushbutton
Type of the driving mechanism		Manual/motorized operating mechanism with mechanical and electrical closing
Type of the driving mechanism / motor drive		Yes
Design of the overcurrent release		ETU25B
General technical data		
Number of poles		4
Size of the circuit-breaker		1
Electrical endurance (switching cycles) / typical		20 000
Usage category		B
circuit-breaker / Design		3WL1106
Mechanical service life (switching cycles) / typical		20 000
Voltage		
Rated insulation voltage Ui	V	1 000
Protection class		
Protection class IP		IP20
Protective function of the overcurrent release		LSI
Dissipation		
Power loss [W]		
• for rated value of the current / at AC / in hot operating state / per pole	W	65
• maximum	W	195
Electricity		
Continuous current / rated value	A	630
Adjustable pick-up value current		
• of instantaneous short-circuit trip unit / initial value	A	12 600
• of instantaneous short-circuit trip unit / Full-scale value	A	12 600
Short-time current resistance (Icw)		

- limited to 0.5 s / rated value
- limited to 1 s / rated value
- limited to 2 s / rated value
- limited to 3 s / rated value

kA	55
kA	42
kA	29.5
kA	24

Main circuit

Operating frequency		
• 1 / rated value	Hz	50
• 2 / rated value	Hz	60
Operating voltage		
• at AC / at 50/60 Hz / rated value	V	690
Operating current		
• at 40 °C / rated value	A	630
• at 50 °C / rated value	A	630
• at 55 °C / rated value	A	630
• at 60 °C / rated value	A	630
• at 65 °C / rated value	A	630
• at 70 °C / rated value	A	630

Suitability

Suitability for use	Plant / motor protection
----------------------------	--------------------------

Product details

Product component		
• Trip indicator		Yes
• Voltage trigger		No
• undervoltage release		Yes
Product extension / optional / motor drive		No

Product function

Product function		
• Ground fault protection		No

Display and operation

Display version	without display
------------------------	-----------------

Short circuit

Operational short-circuit current breaking capacity (Ics)		
• at 415 V / rated value	kA	55
• at 500 V / rated value	kA	55
• at 690 V / rated value	kA	42
Maximum short-circuit current breaking capacity (Icu)		
• at 415 V / rated value	kA	55
• at 500 V / rated value	kA	55
• at 690 V / rated value	kA	42

Connections

Arrangement of electrical connectors / for main current circuit		Main terminal on the rear horizontal
Type of electrical connection / for main current circuit		busbar connection

Mechanical Design

Height	mm	460
Width	mm	410
Depth	mm	456
Mounting type		drawer unit

Environmental conditions

Ambient temperature		
• during operation / minimum	°C	-20
• during operation / maximum	°C	70
• during storage / minimum	°C	-40
• during storage / maximum	°C	70

Certificates

Equipment marking		
• acc. to DIN EN 61346-2		Q
• acc. to DIN EN 81346-2		Q

General Product Approval	Declaration of Conformity	Test Certificates	Shipping Approval
 CCC	 VDE	 EG-Konf.	spezielle Prüfbescheinigungen n sonstig  ABS

Shipping Approval



other

[Umweltbestätigung](#) [sonstig](#)

Further information

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3WL1106-2CB46-6AN2>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3WL1106-2CB46-6AN2/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3WL1106-2CB46-6AN2

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

last modified:

05/29/2017