

WITHDRAW. NON-AUT. CIRCUIT-B. WITH GUIDE FRAME  
3-POLE,  
SIZE I, IEC IN=800A TO 690V,  
AC50/60HZ ICU=66KA AT 500V W. CONNECTION  
FLANGE

### General technical data:

Number of poles

3

### Connections:

Arrangement of electrical connectors

- for main current circuit

with guide frame, connecting flange

### Certificates/approvals:

General Product Approval

EMC

Declaration of Conformity



CB



CCC



GOST



C-TICK



EG-Konf.

### Shipping Approval



ABS



BUREAU  
VERITAS



DNV



GL



LRS

### other

[other](#)

[Environmental  
Confirmations](#)

### Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3WL1108-3A.38-..../all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3WL1108-3A.38-....](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3WL1108-3A.38-....)

CAX-Online-Generator

<http://www.siemens.com/cax>

last change:

Feb 9, 2013