

FIXED-MOUNT NON-AUT. CIRCUIT-B. 3-POLE, SIZE I, IEC IN=1000A TO 690V, AC50/60HZ ICU=55KA AT 500V FRNT.CONN. TOP/BOT. DUAL-HOLE



Model		
product brandname		SENTRON
Product designation		ACB
Design of the operating mechanism		Pushbutton
Type of the driving mechanism		Manual/motorized operating mechanism with mechanical and electrical closing
Type of the driving mechanism / motor drive		Yes
Design of the overcurrent release		without
General technical data		
Number of poles		3
Size of the circuit-breaker		1
Electrical endurance (switching cycles) / typical		20 000
Usage category		B
circuit-breaker / Design		3WL1110
Mechanical service life (switching cycles) / typical		20 000
Voltage		
Rated insulation voltage Ui	V	1 000
Protection class		

Protection class IP		IP20
Protective function of the overcurrent release		without
Dissipation		
Power loss [W]		
• for rated value of the current / at AC / in hot operating state / per pole	W	33.3
• maximum	W	100
Electricity		
Continuous current / rated value	A	1 000
Short-time current resistance (I _{cw})		
• limited to 0.5 s / rated value	kA	55
• limited to 1 s / rated value	kA	42
• limited to 2 s / rated value	kA	29.5
• limited to 3 s / rated value	kA	24
Main circuit		
Operating frequency		
• 1 / rated value	Hz	50
• 2 / rated value	Hz	60
Operating voltage		
• at AC / at 50/60 Hz / rated value	V	690
Operating current		
• at 40 °C / rated value	A	1 000
• at 50 °C / rated value	A	1 000
• at 55 °C / rated value	A	1 000
• at 60 °C / rated value	A	1 000
• at 65 °C / rated value	A	1 000
• at 70 °C / rated value	A	1 000
Suitability		
Suitability for use		Contact unit without release
Product details		
Product component		
• Trip indicator		No
• Voltage trigger		No
• undervoltage release		Yes
Product extension / optional / motor drive		No
Product function		
Product function		
• Ground fault protection		No
Display and operation		

Display version		without display
Short circuit		
Operational short-circuit current breaking capacity (Ics)		
• at 415 V / rated value	kA	55
• at 500 V / rated value	kA	55
• at 690 V / rated value	kA	42
Maximum short-circuit current breaking capacity (Icu)		
• at 415 V / rated value	kA	55
• at 500 V / rated value	kA	55
• at 690 V / rated value	kA	42
Connections		
Arrangement of electrical connectors / for main current circuit		Main connection top front/bottom double hole
Type of electrical connection / for main current circuit		busbar connection
Mechanical Design		
Height	mm	541
Width	mm	320
Depth	mm	369
Mounting type		fixed mounting
Environmental conditions		
Ambient temperature		
• during operation / minimum	°C	-25
• during operation / maximum	°C	70
• during storage / minimum	°C	-40
• during storage / maximum	°C	70
Certificates		
Equipment marking		
• acc. to DIN EN 61346-2		Q
• acc. to DIN EN 81346-2		Q

General Product Approval		Declaration of Conformity	Test Certificates		Shipping Approval
			sonstig	spezielle Prüfbescheinigungen n	
CCC	VDE	EG-Konf.			ABS

Shipping Approval					
					
BUREAU VERITAS	DNV	GL	LRS	PRS	RMRS

other	
Umweltbestätigung	sonstig

Further information

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3WL1110-2AA34-4AN2>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3WL1110-2AA34-4AN2/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)


http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3WL1110-2AA34-4AN2

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



last modified:

02/28/2017