

Draw-out circuit breaker with slide-in module frame 3-pole, Size 1, IEC In=1000 A up to 690 V, 50/60 Hz AC Icu=55 kA at 500 V Rear horizontal connection Overcurrent release ETU 76 LSI protection adjustable 0.4-1 in with graphic display U cubicle bus Communication/ground fault/ ZSS option Motorized/manual operating mechanism with spring charging motor AC 50/60 Hz 208-240 V or 220-250 V DC Activation AC 50/60 Hz 230 V, 220 V DC With 1st auxiliary release Shunt release "F", F1 50/60 Hz 230 V AC/220 V DC, 100% on-load factor without 2nd auxiliary release 4NO+4NC C22= Ready indicator F35= COM35 module, PROFINET IO - Modbus TCP, with breaker status sensor F36= Metering PLUS Voltage-tap bottom side I, U, P, W, Q, f, cos phi, harmonics, THD, R15= Position signaling switch, withdrawable part 3 changeover contacts R21= Shutter 2-part can be locked with padlock

Further information

Industry Online Support (Manuals, Catalogs, Certificates, FAQ, ...)
<https://support.industry.siemens.com/cs/products?mfn=ps&lc=en-WW>
Industry Mall (Online ordering system)
<https://mall.industry.siemens.com>

