

Draw-out circuit breaker with slide-in module frame 3-pole, Size 1, IEC In=1250 A
up to 690 V, 50/60 Hz AC Icu=55 kA at 500 V Rear horizontal connection
Overcurrent release ETU 15 LI protection adjustable 0.5-1 in With manual
operating mechanism with storage with mechanical request without 1st auxiliary
release without 2nd auxiliary release 2NO+2NC F12= COM16 Modbus module with
breaker status sensor F36= Metering PLUS Voltage-tap bottom side I, U, P, W, Q, f,
cos phi, harmonics, THD,

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3WL1112-2BB66-1AA2-Z F12+F36>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3WL1112-2BB66-1AA2-Z F12+F36>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3WL1112-2BB66-1AA2-Z F12+F36

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



last modified:

4/6/2024

