

fixed-mounted circuit breaker 3-pole, size I, IEC In=1250A to 690V, AC50/60Hz
Icu=55kA at 500V frnt.conn. top/bot. dual-hole Overcurrent release ETU 25 LSI
protection adjustable 0.4-1 in Motorized/manual operating mechanism with spring
charging motor AC 50/60 Hz 110-127 V AC or 110-125 V DC Activation 50/60 Hz
110 V AC, 110 V DC without 1st auxiliary release With 2nd auxiliary release "R",
F3 Undervoltage, instant. 110-127 V AC, 110-125 V DC 2NO+2NC C01=
mechanical switching cycle counter F31= EMC filter S07= Locking device in OFF
position w. 4 bracket locks (safe OFF/disconnector functionality) Disconnector
condition IEC 60947-2

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3WL1112-2CB34-5AM2-Z C01+F31+S07>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3WL1112-2CB34-5AM2-Z C01+F31+S07>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3WL1112-2CB34-5AM2-Z C01+F31+S07

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



last modified:

1/18/2024

