

FIXED-MOUNTED CIRCUIT BREAKER 4-POLE,  
 SIZE I, IEC IN=1250A TO 690V,  
 AC50/60HZ ICU=66KA AT 500V FRNT.CONN. TOP/BOT.  
 SINGLE-HOLE

**General technical data:**

|                 |   |
|-----------------|---|
| Number of poles | 4 |
|-----------------|---|

**Connections:**

|  |                                    |
|--|------------------------------------|
| Arrangement of electrical connectors                                       | main connection front, single hole |
| <ul style="list-style-type: none"> <li>for main current circuit</li> </ul> |                                    |

**Certificates/approvals:**

| General Product Approval | EMC | Declaration of Conformity |
|--------------------------|-----|---------------------------|
|--------------------------|-----|---------------------------|



**Shipping Approval**



**other**

[other](#)

[Environmental Confirmations](#)

**Further information:**

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<http://www.siemens.com/lowvoltage/maill>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<http://support.automation.siemens.com/WW/view/en/3WL1112-3..43-..../all>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3WL1112-3..43-....](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3WL1112-3..43-....)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

last change:

Feb 9, 2013