

withdrawable circuit breaker without guide frame 3-pole, size I, IEC In=1250A to 690V, AC50/60Hz Icu=66kA at 500V rear connection horizontal Overcurrent release ETU 27 LSING protection adjustable 0.4-1 in Ground fault/N protection integrated Motorized/manual operating mechanism with memory Drive motor AC 50/60 Hz 110-127 V AC or 110-125 V DC Activation 50/60 Hz 110 V AC, 110 V DC With 1st auxiliary release Shunt release "F", F1 50/60 Hz 110 V AC/110 V DC, 100% on-load factor without 2nd auxiliary release 4NO+4NC



Model		
Product brand name		SENTRON
Product designation		ACB
Design of the product		IEC 60947-2
Design of the auxiliary switch		4 NO + 4 NC
Design of the operating mechanism		Pushbutton

Type of the driving mechanism		Manual/motorized operating mechanism with mechanical and electrical closing
Type of the driving mechanism / motor drive		Yes
Design of the overcurrent release		ETU27B

General technical data

Number of poles		3
Size of the circuit-breaker		1
Electrical endurance (switching cycles) / typical		20 000
Usage category		B
circuit-breaker / Design		3WL1
Mechanical service life (switching cycles) / typical		20 000

Voltage

Rated insulation voltage Ui	V	1 000
-----------------------------	---	-------

Protection class

Protection class IP		IP20
Protective function of the overcurrent release		LSING

Dissipation

Power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	W	68.3
---	---	------

Electricity

Operating current / at 45 °C / rated value	A	1 250
Continuous current / rated value	A	1 250
Adjustable pick-up value current		
• of the current-dependent overload release / Full-scale value	A	1 250
• of instantaneous short-circuit trip unit / initial value	A	25 000
• of instantaneous short-circuit trip unit / Full-scale value	A	25 000
Short-time current resistance (Icw)		
• limited to 0.5 s / rated value	kA	66
• limited to 1 s / rated value	kA	50
• limited to 2 s / rated value	kA	35
• limited to 3 s / rated value	kA	29

Main circuit

Operating frequency		
• 1 / rated value	Hz	50
• 2 / rated value	Hz	60
Operating voltage		
• at AC / at 50/60 Hz / rated value	V	690
Operating current		

• at 40 °C / rated value	A	1 250
• at 50 °C / rated value	A	1 250
• at 55 °C / rated value	A	1 250
• at 60 °C / rated value	A	1 250
• at 65 °C / rated value	A	1 250
• at 70 °C / rated value	A	1 210

Auxiliary circuit

Number of NC contacts / for auxiliary contacts		4
Number of NO contacts / for auxiliary contacts		4

Suitability

Suitability for use		Plant / motor protection
---------------------	--	--------------------------

Adjustable parameters

Adjustable pick-up value current / of the current-dependent overload release / initial value	A	500
--	---	-----

Product details

Product component		
• Trip indicator		Yes
• Voltage trigger		Yes
• undervoltage release		No
Product extension / optional / motor drive		No

Product function

Product function		
• Ground fault protection		Yes
• Phase failure detection		Yes

Display and operation

Display version		without display
-----------------	--	-----------------

Short circuit

Operational short-circuit current breaking capacity (Ics)		
• at 415 V / rated value	kA	66
• at 500 V / rated value	kA	66
• at 690 V / rated value	kA	50
Maximum short-circuit current breaking capacity (Icu)		
• at 415 V / rated value	kA	66
• at 500 V / rated value	kA	66
• at 690 V / rated value	kA	50

Connections

Arrangement of electrical connectors / for main current circuit		without guide frame
---	--	---------------------

Type of electrical connection / for main current circuit		Blade contacts
--	--	----------------

Mechanical Design

Height	mm	411.5
Width	mm	311
Depth	mm	337
Mounting type		drawer unit

Environmental conditions

Ambient temperature		
• during operation / minimum	°C	-20
• during operation / maximum	°C	70
• during storage / minimum	°C	-40
• during storage / maximum	°C	70

Certificates

Reference code		
• acc. to DIN EN 61346-2		Q
• acc. to DIN EN 81346-2		Q
Waste electronic equipment must not be disposed as unsorted municipal waste, e.g. household waste. For disposing the waste electronic equipment it is necessary to observe the current local national/international regulations. 		

General Product Approval			Declaration of Conformity	Test Certificates	
				Miscellaneous	Special Test Certificate
CB	CCC	VDE	EG-Konf.		

Shipping Approval					
					
ABS	BUREAU VERITAS	DNV	GL	LRS	PRS

Shipping Approval	other		
	Environmental Conformations	Manufacturer Declaration	Miscellaneous
RMRS			

Further information

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3WL1112-3DG35-5FA4>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3WL1112-3DG35-5FA4>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)





http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3WL1112-3DG35-5FA4


CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>





last modified:

02/20/2019