

WITHDRAWABLE CIRCUIT BREAKER WITHOUT GUIDE FRAME 4-POLE, SIZE I, IEC IN=1250A TO 690V, AC50/60HZ ICU=66KA AT 500V REAR CONNECTION HORIZONTAL

Model		
product brandname		SENTRON
Product designation		ACB
Design of the operating mechanism		Pushbutton
Type of the driving mechanism		Manual/motorized operating mechanism with mechanical and electrical closing
Type of the driving mechanism / motor drive		Yes
Design of the overcurrent release		ETU45B

General technical data		
Number of poles		4
Size of the circuit-breaker		1
Electrical endurance (switching cycles) / typical		20 000
Usage category		B
circuit-breaker / Design		3WL1112
Mechanical service life (switching cycles) / typical		20 000

Voltage		
Rated insulation voltage U_i	V	1 000
Insulation voltage / rated value	V	1 000

Protection class		
Protection class IP		IP20
Protective function of the overcurrent release		LSIN

Dissipation		
Power loss [W]		
<ul style="list-style-type: none"> for rated value of the current / at AC / in hot operating state / per pole 	W	68.3
<ul style="list-style-type: none"> maximum 	W	205

Electricity		
Continuous current / rated value	A	1 250
Adjustable pick-up value current		
<ul style="list-style-type: none"> of instantaneous short-circuit trip unit / initial value 	A	1 875
<ul style="list-style-type: none"> of instantaneous short-circuit trip unit / Full-scale value 	A	15 000

Short-time current resistance (I_{cw})		
• limited to 0.5 s / rated value	kA	66
• limited to 1 s / rated value	kA	50
• limited to 2 s / rated value	kA	35
• limited to 3 s / rated value	kA	29

Main circuit

Operating frequency		
• 1 / rated value	Hz	50
• 2 / rated value	Hz	60
Operating voltage		
• at AC / at 50/60 Hz / rated value	V	690
Operating current		
• at 40 °C / rated value	A	1 250
• at 50 °C / rated value	A	1 250
• at 55 °C / rated value	A	1 250
• at 60 °C / rated value	A	1 250
• at 65 °C / rated value	A	1 250
• at 70 °C / rated value	A	1 210

Suitability

Suitability for use	Plant / motor protection
----------------------------	--------------------------

Product details

Product component		
• Trip indicator		Yes
• Voltage trigger		Yes
• undervoltage release		No
Product extension / optional / motor drive		No

Product function

Product function		
• Ground fault protection		No

Display and operation

Display version	without display
------------------------	-----------------

Short circuit

Operational short-circuit current breaking capacity (I_{cs})		
• at 415 V / rated value	kA	66
• at 500 V / rated value	kA	66
• at 690 V / rated value	kA	50
Maximum short-circuit current breaking capacity (I_{cu})		
• at 415 V / rated value	kA	66
• at 500 V / rated value	kA	66

• at 690 V / rated value

kA	50
----	----

Connections

Arrangement of electrical connectors / for main current circuit		without guide frame
Type of electrical connection / for main current circuit		Blade contacts

Mechanical Design

Height	mm	411.5
Width	mm	401
Depth	mm	337
Mounting type		drawer unit

Environmental conditions

Ambient temperature		
• during operation / minimum	°C	-20
• during operation / maximum	°C	55
• during storage / minimum	°C	-40
• during storage / maximum	°C	70

Certificates

Equipment marking		
• acc. to DIN EN 61346-2		Q
• acc. to DIN EN 81346-2		Q

General Product Approval	Declaration of Conformity	Test Certificates
--------------------------	---------------------------	-------------------



[sonstig](#)

Test Certificates	Shipping Approval
-------------------	-------------------

[spezielle Prüfbescheinigung](#)
n



Shipping Approval	other
-------------------	-------



[Umweltbestätigung](#)

[sonstig](#)

Further information

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3WL1112-3EB45-5FA4-Z B12+C11+F20+K07>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3WL1112-3EB45-5FA4-Z B12+C11+F20+K07/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mfb=3WL1112-3EB45-5FA4-Z B12+C11+F20+K07

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

last modified:

10/20/2016