

fixed-mounted circuit breaker 3-pole, size II, IEC In=1000A to 690V, AC50/60Hz
Icu=100kA at 500V frnt.conn. top/bot. dual-hole Overcurrent release ETU 15 LI
protection adjustable 0.5-1 in Motorized/manual operating mechanism with spring
charging motor AC 50/60 Hz 208-240 V or 220-250 V DC Activation AC 50/60 Hz
230 V, 220 V DC without 1st auxiliary release With 2nd auxiliary release "R", F3
Undervoltage, instant. 208-240 V AC, 220-250 V DC 2NO+2NC F31= EMC filter

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3WL1210-4BB34-4AN2-Z F31>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3WL1210-4BB34-4AN2-Z F31>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3WL1210-4BB34-4AN2-Z F31

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



