

fixed-mount non-aut. circuit-b. 3-pole, size II, IEC In=1250A to 690V, AC50/60Hz
Icu=80kA at 500V rear connection horizontal without overcurrent release
Motorized/manual operating mechanism with spring charging motor AC 50/60 Hz
208-240 V or 220-250 V DC Activation AC 50/60 Hz 230 V, 220 V DC With 1st
auxiliary release Shunt release "F", F1 50/60 Hz 230 V AC/220 V DC, 100% on-
load factor With 2nd auxiliary release "R", F3 Undervoltage, instant. 208-240 V AC,
220-250 V DC 4NO+4NC F40= Sealing disc for ETU25-76 for protection against
unauthorized operation K07= Caution!!! Order code K07 with non-automatic circuit
breaker not possible!!! T40= Door sealing frame

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3WL1212-3AA32-4GN4-Z F40+K07+T40>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3WL1212-3AA32-4GN4-Z F40+K07+T40>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3WL1212-3AA32-4GN4-Z F40+K07+T40

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



