

WITHDRAWABLE CIRCUIT BREAKER WITH GUIDE
 FRAME 3-POLE,
 SIZE II, IEC IN=1250A TO 690V,
 AC50/60HZ ICU=100KA AT 500V REAR CONNECTION
 VERTICAL






General technical data:

Number of poles	3
------------------------	---





Connections:

Arrangement of electrical connectors	with guide frame, main connection vertical
<ul style="list-style-type: none"> for main current circuit 	

Certificates/approvals:

General Product Approval		EMC		Declaration of Conformity
				
CB	CCC	GOST	C-TICK	EG-Konf.

Shipping Approval

				
ABS	BUREAU VERITAS	DNV	GL	LRS

other

other	Environmental Confirmations
-----------------------	---

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WWW/view/en/3WL1212-4..37-..../all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3WL1212-4..37-....

CAX-Online-Generator

<http://www.siemens.com/cax>

last change:

Feb 9, 2013