

WITHDRAWABLE CIRCUIT BREAKER WITH GUIDE
FRAME 3-POLE,
SIZE II, IEC IN=1600A TO 690V,
AC50/60HZ ICU=80KA AT 500V REAR CONNECTION
VERTICAL

General technical data:

Number of poles

3

Connections:

Arrangement of electrical connectors

- for main current circuit

with guide frame, main connection vertical

Certificates/approvals:

General Product Approval

EMC

Declaration of Conformity



CB



CCC



GOST



C-TICK



EG-Konf.

Shipping Approval



ABS



BUREAU
VERITAS



DNV



GL



LRS

other

[other](#)

[Environmental
Confirmations](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3WL1216-3..37-..../all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3WL1216-3..37-....

CAX-Online-Generator

<http://www.siemens.com/cax>

last change:

Feb 9, 2013