

withdrawable circuit breaker without guide frame 3-pole, size II, IEC
In=1600A to 690V, AC50/60Hz Icu=80kA at 500V rear connection
horizontal Overcurrent release ETU 45 LSIN protection adjustable 0.4-1 in
with cubicle bus Opt.: Comm. /measuring func./ground fault/ ZSS With
manual operating mechanism with storage with mechanical request without
1st auxiliary release without 2nd auxiliary release 2NO+2NC

Model	
product brand name	SENTRON
product designation	ACB
design of the product	IEC 60947-2
design of the actuating element	Pushbutton
type of the driving mechanism	Manual operating mechanism with mechanical closing
type of the driving mechanism / motor drive	No
design of the overcurrent release	ETU45B
General technical data	
number of poles	3
size of the circuit-breaker	2
utilization category	B
circuit-breaker / Design	3WL1
Voltage	
Rated insulation voltage Ui	1 000 V
insulation voltage / rated value	1 000 V
operating voltage	
• at AC / at 50/60 Hz / rated value	690 V
Protection class	
protection class IP	IP20
protection class IP / on the front	IP20
protection function of the overcurrent release	LSIN
Dissipation	
power loss [W]	
• for rated value of the current / at AC / in hot operating state / per pole	58.7 W
• maximum	175 W
Current	
operational current	
• at 40 °C / rated value	1 600 A
• at 45 °C / rated value	1 600 A
• at 50 °C / rated value	1 600 A
• at 55 °C / rated value	1 600 A
• at 60 °C / rated value	1 600 A
• at 65 °C / rated value	1 600 A
• at 70 °C / rated value	1 600 A
continuous current / rated value / maximum	1 600 A
continuous current / rated value	1 600 A
adjustable current response value current	
• of the current-dependent overload release / full-scale value	1 600 A
• of instantaneous short-circuit trip unit / minimum	2 400 A
• of instantaneous short-circuit trip unit / maximum	19 200 A
Main circuit	
operating frequency	
• 1 / rated value	50 Hz
• 2 / rated value	60 Hz

Auxiliary circuit		
number of NC contacts / for auxiliary contacts	2	
number of NO contacts / for auxiliary contacts	2	
Suitability		
suitability for use	Plant / motor protection	
Adjustable parameters		
adjustable current response value current - of the L-trip / with I4t characteristic / initial value - of the L-trip / with I4t characteristic / full-scale value	640 A 1 600 A	
adjustable current response value current / of the current-dependent overload release / initial value	640 A	
Product details		
product component - trip indicator - voltage trigger - undervoltage release	Yes No No	
design of the auxiliary switch	2 NO + 2 NC	
product extension / optional / motor drive	Yes	
Product function		
product function - grounding protection - phase failure detection	No Yes	
Display and operation		
display version	without display	
Short circuit		
breaking capacity operating short-circuit current (Ics) - at 415 V / rated value - at 500 V / rated value - at 690 V / rated value	80 kA 80 kA 75 kA	
breaking capacity maximum short-circuit current (Icu) - at 415 V / rated value - at 500 V / rated value - at 690 V / rated value	80 kA 80 kA 75 kA	
Connections		
arrangement of electrical connectors / for main current circuit	without guide frame	
type of electrical connection / for main current circuit	Blade contacts	
Mechanical Design		
height	411.5 mm	
width	451 mm	
depth	337 mm	
fastening method	drawer unit	
Environmental conditions		
ambient temperature / during operation - minimum - maximum	-20 °C 70 °C	
ambient temperature / during storage - minimum - maximum	-40 °C 70 °C	
General Product Approval	EMC	Declaration of Conformity



[Confirmation](#)



EG-Konf.

Test Certificates

Marine / Shipping

[Type Test Certificates/Test Report](#)

[Special Test Certificate](#)

[Miscellaneous](#)



Marine / Shipping

other



[CCS / China Classification Society](#)



[Environmental Confirmations](#)

[Miscellaneous](#)

[Confirmation](#)

other

Dangerous Good

[Miscellaneous](#)

[Transport Information](#)

Further information

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3WL1216-3EB35-1AA2>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3WL1216-3EB35-1AA2>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)





http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3WL1216-3EB35-1AA2


CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>





L (Long Time Delay / Überlastschutz); S (Short Time Delay / Kurzschlusschutz, kurzzeitverzögert);
 I (Instantaneous / Kurzschlusschutz, unverzögert); N (Neutral Protection / Neutralleiterschutz); F5 (Magnet for trip unit / Auslösemagnet);
 S1 - S8 (Auxiliary switch / Hilfschalter);

last modified:

3/23/2020 