

Fixed-mounted circuit breaker 3-pole, Size 2, IEC In=2500 A to 690 V, 50/60 Hz  
AC Icu=66 kA at 500 V Rear horizontal connection Overcurrent release ETU 25  
LSI protection adjustable 0.4-1 in Motorized/manual operating mechanism with  
spring charging motor AC 50/60 Hz 208-240 V or 220-250 V DC Activation AC  
50/60 Hz 230 V, 220 V DC With 1st auxiliary release Shunt release "F", F1 50/60  
Hz 230 V AC/220 V DC, 100% on-load factor without 2nd auxiliary release  
4NO+4NC S08= RONIS locking device in Off position (safe OFF/disconnector  
functionality) Disconnector condition in compliance with IEC 60947-2 Disconnector  
condition in compliance with IEC 60947-2

### Further information

#### Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

#### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3WL1225-2CB62-4GA4-Z S08>

#### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3WL1225-2CB62-4GA4-Z S08>

#### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3WL1225-2CB62-4GA4-Z S08](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3WL1225-2CB62-4GA4-Z S08)

#### CAX-Online-Generator

<http://www.siemens.com/cax>

#### Tender specifications

<http://www.siemens.com/specifications>



last modified:

1/17/2024

