

FIXED-MOUNTED CIRCUIT BREAKER 4-POLE,
 SIZE II, IEC IN=3200A TO 690V,
 AC50/60HZ ICU=66KA AT 500V REAR CONNECTION
 VERTICAL

General technical data:

Number of poles	4
-----------------	---

Connections:

Arrangement of electrical connectors	main connection vertical
<ul style="list-style-type: none"> for main current circuit 	

Certificates/approvals:

General Product Approval	EMC	Declaration of Conformity
--------------------------	-----	---------------------------



Shipping Approval



other

[other](#)

[Environmental Confirmations](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/maill>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3WL1232-2..41-..../all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3WL1232-2..41-....

CAX-Online-Generator

<http://www.siemens.com/cax>

last change:

Feb 9, 2013