

WITHDRAWABLE CIRCUIT BREAKER WITHOUT  
GUIDE FRAME 3-POLE, SIZE II, IEC IN=3200A TO  
690V, AC50/60HZ ICU=100KA AT 500V REAR  
CONNECTION HORIZONTAL

| Model                                                                        |   |                                                                             |
|------------------------------------------------------------------------------|---|-----------------------------------------------------------------------------|
| product brandname                                                            |   | SENTRON                                                                     |
| Product designation                                                          |   | ACB                                                                         |
| Design of the operating mechanism                                            |   | Pushbutton                                                                  |
| Type of the driving mechanism                                                |   | Manual/motorized operating mechanism with mechanical and electrical closing |
| Type of the driving mechanism / motor drive                                  |   | Yes                                                                         |
| Design of the overcurrent release                                            |   | ETU45B                                                                      |
| General technical data                                                       |   |                                                                             |
| Number of poles                                                              |   | 3                                                                           |
| Size of the circuit-breaker                                                  |   | 2                                                                           |
| Electrical endurance (switching cycles) / typical                            |   | 15 000                                                                      |
| Usage category                                                               |   | B                                                                           |
| circuit-breaker / Design                                                     |   | 3WL1232                                                                     |
| Mechanical service life (switching cycles) / typical                         |   | 15 000                                                                      |
| Voltage                                                                      |   |                                                                             |
| Rated insulation voltage $U_i$                                               | V | 1 000                                                                       |
| Insulation voltage / rated value                                             | V | 1 000                                                                       |
| Protection class                                                             |   |                                                                             |
| Protection class IP                                                          |   | IP20                                                                        |
| Protective function of the overcurrent release                               |   | LSIN                                                                        |
| Dissipation                                                                  |   |                                                                             |
| Power loss [W]                                                               |   |                                                                             |
| • for rated value of the current / at AC / in hot operating state / per pole | W | 236.7                                                                       |
| • maximum                                                                    | W | 710                                                                         |
| Electricity                                                                  |   |                                                                             |
| Continuous current / rated value                                             | A | 3 200                                                                       |
| Adjustable pick-up value current                                             |   |                                                                             |
| • of instantaneous short-circuit trip unit / initial value                   | A | 4 800                                                                       |
| • of instantaneous short-circuit trip unit / Full-scale value                | A | 38 400                                                                      |

|                                                                             |    |                          |
|-----------------------------------------------------------------------------|----|--------------------------|
| <b>Short-time current resistance (I<sub>cw</sub>)</b>                       |    |                          |
| • limited to 0.5 s / rated value                                            | kA | 100                      |
| • limited to 1 s / rated value                                              | kA | 85                       |
| • limited to 2 s / rated value                                              | kA | 70                       |
| • limited to 3 s / rated value                                              | kA | 65                       |
| <b>Main circuit</b>                                                         |    |                          |
| <b>Operating frequency</b>                                                  |    |                          |
| • 1 / rated value                                                           | Hz | 50                       |
| • 2 / rated value                                                           | Hz | 60                       |
| <b>Operating voltage</b>                                                    |    |                          |
| • at AC / at 50/60 Hz / rated value                                         | V  | 690                      |
| <b>Operating current</b>                                                    |    |                          |
| • at 40 °C / rated value                                                    | A  | 3 200                    |
| • at 50 °C / rated value                                                    | A  | 3 200                    |
| • at 55 °C / rated value                                                    | A  | 3 200                    |
| • at 60 °C / rated value                                                    | A  | 3 020                    |
| • at 65 °C / rated value                                                    | A  | 3 020                    |
| • at 70 °C / rated value                                                    | A  | 2 870                    |
| <b>Auxiliary circuit</b>                                                    |    |                          |
| <b>Number of NC contacts / for auxiliary contacts</b>                       |    | 4                        |
| <b>Number of NO contacts / for auxiliary contacts</b>                       |    | 4                        |
| <b>Suitability</b>                                                          |    |                          |
| <b>Suitability for use</b>                                                  |    | Plant / motor protection |
| <b>Product details</b>                                                      |    |                          |
| <b>Product component</b>                                                    |    |                          |
| • Trip indicator                                                            |    | Yes                      |
| • Voltage trigger                                                           |    | Yes                      |
| • undervoltage release                                                      |    | No                       |
| Product extension / optional / motor drive                                  |    | No                       |
| <b>Product function</b>                                                     |    |                          |
| <b>Product function</b>                                                     |    |                          |
| • Ground fault protection                                                   |    | No                       |
| <b>Display and operation</b>                                                |    |                          |
| <b>Display version</b>                                                      |    | without display          |
| <b>Short circuit</b>                                                        |    |                          |
| <b>Operational short-circuit current breaking capacity (I<sub>cs</sub>)</b> |    |                          |
| • at 415 V / rated value                                                    | kA | 100                      |
| • at 500 V / rated value                                                    | kA | 100                      |

|                                                              |    |     |
|--------------------------------------------------------------|----|-----|
| • at 690 V / rated value                                     | kA | 85  |
| <b>Maximum short-circuit current breaking capacity (Icu)</b> |    |     |
| • at 415 V / rated value                                     | kA | 100 |
| • at 500 V / rated value                                     | kA | 100 |
| • at 690 V / rated value                                     | kA | 85  |
| • at 1000/1150 V / rated value                               | kA | 50  |
| <b>Short-circuit current making capacity (Icm)</b>           |    |     |
| • at 415 V / rated value                                     | kA | 220 |
| • at 500 V / rated value                                     | kA | 220 |
| • at 690 V / rated value                                     | kA | 187 |
| • at 1000/1150 V / rated value                               | kA | 105 |

#### Connections

|                                                                 |  |                     |
|-----------------------------------------------------------------|--|---------------------|
| Arrangement of electrical connectors / for main current circuit |  | without guide frame |
| Type of electrical connection / for main current circuit        |  | Blade contacts      |

#### Mechanical Design

|                      |    |             |
|----------------------|----|-------------|
| <b>Height</b>        | mm | 411.5       |
| <b>Width</b>         | mm | 451         |
| <b>Depth</b>         | mm | 337         |
| <b>Mounting type</b> |    | drawer unit |

#### Environmental conditions

|                              |    |     |
|------------------------------|----|-----|
| <b>Ambient temperature</b>   |    |     |
| • during operation / minimum | °C | -20 |
| • during operation / maximum | °C | 55  |
| • during storage / minimum   | °C | -40 |
| • during storage / maximum   | °C | 70  |

#### Certificates

|                          |  |   |
|--------------------------|--|---|
| <b>Equipment marking</b> |  |   |
| • acc. to DIN EN 61346-2 |  | Q |
| • acc. to DIN EN 81346-2 |  | Q |

| General Product Approval                                                                 |                                                                                          | Declaration of Conformity                                                         | Test Certificates                                                                             |                                                                                               |
|------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------|
| <br>CCC | <br>VDE |  | <br>EG-Konf. | <a href="#">sonstig</a><br><a href="#">spezielle Prüfbescheinigungen</a><br><a href="#">n</a> |

| Shipping Approval                                                                        |                                                                                                     |                                                                                         |                                                                                          |                                                                                            |                                                                                             |
|------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|
| <br>ABS | <br>BUREAU VERITAS | <br>GL | <br>LRS | <br>PRS | <br>RMRS |

| other                             |                         |
|-----------------------------------|-------------------------|
| <a href="#">Umweltbestätigung</a> | <a href="#">sonstig</a> |

#### Further information

##### Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3WL1232-4EB35-4GA4>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3WL1232-4EB35-4GA4/all>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3WL1232-4EB35-4GA4](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3WL1232-4EB35-4GA4)

##### CAX-Online-Generator

<http://www.siemens.com/cax>

##### Tender specifications

<http://ausschreibungstexte.siemens.com/tiplv>

last modified:

10/15/2016