

Draw-out circuit breaker Without guide frame 4-pole, Size 3, IEC In=5000 A up to 690 V, 50/60 Hz AC Icu=100 kA at 500 V Rear horizontal connection Overcurrent release ETU 45 LSING protection adjustable 0.4-1 in with display and cubicle bus with ground fault protection Opt.: Comm./measuring func./ZSS Motorized/manual operating mechanism with spring charging motor AC 50/60 Hz 208-240 V or 220-250 V DC Activation AC 50/60 Hz 230 V, 220 V DC With 1st auxiliary release Shunt release "F", F1 50/60 Hz 230 V AC/220 V DC, 100% on-load factor With 2nd auxiliary release "R", F3 Undervoltage, instant. 50/60 Hz 380-415 V AC 4NO+4NC F02= COM15 PROFIBUS module with breaker status sensor F23= Internal current converter 4-pole switch BGIII F40= Sealing disc for ETU25-76 for protection against unauthorized operation R15= Position signaling switch, withdrawable part 3 changeover contacts R21= Shutter 2-part can be locked with bracket lock T40= Door sealing frame

Further information

Industry Online Support (Manuals, Catalogs, Certificates, FAQ, ...)
<https://support.industry.siemens.com/cs/products?mfn=ps&lc=en-WW>
Industry Mall (Online ordering system)
<https://mall.industry.siemens.com>

