



Removable terminal 3-pole, push-in terminals up to maximal 2 x 1.5 mm<sup>2</sup>  
For SIRIUS devices in industrial standard mounting rail enclosure

|                                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|----------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| product brand name                           | SIRIUS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| product category                             | Removable terminals                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| product designation                          | Terminal for control circuit/3-pole                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| design of the product                        | Spring-loaded terminal (push-in)/up to max. 2 x 1.5 mm <sup>2</sup>                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>General technical data</b>                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| protection class IP                          | IP20                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Substance Prohibitance (Date)                | 01.03.2017                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| type of connectable conductor cross-sections | <ul style="list-style-type: none"> <li>• solid 1x (0.5 ... 1.5 mm<sup>2</sup>), 2x (0.5 ... 1.5 mm<sup>2</sup>)</li> <li>• finely stranded with core end processing 1x (0.5 ... 1.0 mm<sup>2</sup>), 2x (0.5 ... 1.0 mm<sup>2</sup>)</li> <li>• finely stranded without core end processing 1x (0.5 ... 1.5 mm<sup>2</sup>), 2x (0.5 ... 1.5 mm<sup>2</sup>)</li> <li>• at AWG cables solid 1x (20 ... 16), 2x (20 ... 16)</li> <li>• at AWG cables stranded 1x (20 ... 16), 2x (20 ... 16)</li> </ul> |
| width                                        | 7.5 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |

### Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3ZY1131-2BA00>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3ZY1131-2BA00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)



<https://support.industry.siemens.com/cs/ww/en/ps/3ZY1131-2BA00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3ZY1131-2BA00&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3ZY1131-2BA00&lang=en)

Characteristic: Derating

<https://support.industry.siemens.com/cs/ww/en/ps/3ZY1131-2BA00/manual>



last modified:

1/28/2021 