

# Ball valve VZBE-1-T-63-D-2-M-V15V15

Part number: 4745219

**FESTO**



[PDF](#) General operating condition

## Data sheet

| Feature                                                                 | Value                                                                                          |
|-------------------------------------------------------------------------|------------------------------------------------------------------------------------------------|
| Structural design                                                       | 2-way ball valve with hand lever                                                               |
| Actuation type                                                          | Mechanical                                                                                     |
| Sealing principle                                                       | Soft                                                                                           |
| Mounting position                                                       | Any                                                                                            |
| Type of mounting                                                        | Line installation                                                                              |
| Fitting connection                                                      | 1 NPT                                                                                          |
| Switching position indication                                           | Slot direction = flow direction                                                                |
| Inside diameter                                                         | 25 mm                                                                                          |
| Nominal width DN                                                        | 25                                                                                             |
| Valve function                                                          | 2/2                                                                                            |
| Flow direction                                                          | Reversible                                                                                     |
| Nominal pressure of fitting PN                                          | 63                                                                                             |
| Breakaway torque at differential pressure, nominal pressure, fitting PN | 11 Nm                                                                                          |
| Based on norm                                                           | ASME B1.20.1                                                                                   |
| Symbol                                                                  | 00991458                                                                                       |
| Medium                                                                  | Vapor<br>Compressed air as per ISO 8573-1:2010 [-:~:]<br>Inert gas<br>Water<br>Neutral liquids |
| Temperature of medium                                                   | -20 °C ... 200 °C                                                                              |
| Flow rate Kv                                                            | 94 m³/h                                                                                        |
| Note on materials                                                       | RoHS-compliant                                                                                 |
| LABS (PWIS) conformity                                                  | VDMA24364 zone III                                                                             |
| Housing material                                                        | Cast stainless steel                                                                           |
| Material number of housing                                              | 1.4408                                                                                         |
| Seat seal material                                                      | PTFE                                                                                           |
| Seals material                                                          | PTFE                                                                                           |
| Ball material                                                           | Cast stainless steel                                                                           |
| Material number for ball                                                | 1.4408                                                                                         |

| Feature                             | Value                                                              |
|-------------------------------------|--------------------------------------------------------------------|
| Shaft material                      | High-alloy stainless steel                                         |
| Material number for shaft           | 1.4401                                                             |
| Product weight                      | 800 g                                                              |
| Certification                       | CRN                                                                |
| Explosion prevention and protection | Zone 1 (ATEX)<br>Zone 2 (ATEX)<br>Zone 21 (ATEX)<br>Zone 22 (ATEX) |
| Corrosion resistance class (CRC)    | 3 - High corrosion stress                                          |