

TRANSFO FOR CONTINUOUS LOAD PRIM 230 V 50 HZ SEC 8 V AC 8 VA, WITH PTC PROT.



Figure similar

Model		
product brand name		SETRON
Design of the transformer		Power transformer
General technical data		
Supplied active power / maximum	W	8
Voltage		
Output voltage		
• _1 / rated value	V	8
• _2 / rated value	V	0
• _3 / rated value	V	0
Dissipation		
Power loss [W]		
• for rated value of the current / at AC / in hot operating state / per pole	W	3
• maximum	W	2.6
Electricity		

Output current		
• maximum	A	1
• _1 / rated value	A	1
• _2 / rated value	A	0
• _3 / rated value	A	0

Suitability

Suitability for integration		
• surface-mounted installation		No
• flush mounting		No

Product details

Product component / switch		No
----------------------------	--	----

Product function

Product function / Thermal protection		Yes
---------------------------------------	--	-----

Inputs Outputs

Property of the output / Short-circuit proof		Yes
--	--	-----

Mechanical Design

Height	mm	64
Width	mm	54
Length	mm	90
Number of width units		3
Mounting type / Side-by-side mounting		Yes

General Product Approval



Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/4AC3408>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/4AC3408/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=4AC3408

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://ausschreibungstexte.siemens.com/tiplv>





Figure similar



last modified:

08/11/2016