

TRANSFORMER SITAS;
 PHASES:1;
 PN/PN(S6)(KVA):6,3 /22,5;
 UPRI(V):400-230+/-15;
 USEC(V):230-115;
 ISEC(A):27,3-54,7;
 F(HZ):50...60;
 VECTOR GR./SHIELD WNG.:II0 /0;
 TA/ISOKL:55 /H;
 IP00;
 TYPE OF TERMINALS:SCREW CONNECTION;
 INSTALLATION:SCREW;
 EN 61558-2-1, -2-2,
 -2-4 >UL/CSA-RECOGNIZED< >CONTROL CIRCUIT
 TRANSFORMER< >ISOLATION TRANSFORMER<

General technical details:

Product designation		transformer SITAS
product brand name		SIDAC
Operating apparent output / rated value	V·A	6,300
Efficiency		0.94
Manner of switching for transformers		II0
Verification of suitability		CE
Product function		
• temperature surveillance		No
• isolation control		No
• short circuit and overload protection		No
Number of the protective coils		0
Short-term vector power	V·A	24,500
Relative short-circuit voltage	%	3.2

Inputs:

Phase number / of the inputs		1
Input voltage		
• _1 / rated value	V	415
• _2 / rated value	V	400
• _3 / rated value	V	385
• _4 / rated value	V	245
• _5 / rated value	V	230
• _6 / rated value	V	215

Electrical input frequency		
	• minimum	Hz 50
	• maximum	Hz 60

Outputs:

Phase number / of the outputs		1
Output voltage	• _1 / rated value	V 230
	• _2 / rated value	V 115
Electrical output frequency	• maximum	Hz 60
	• minimum	Hz 50

Ambient conditions:

Thermal class / according to IEC 60085		H
Ambient temperature / rated value	°C	55
Protection class IP		IP00

Mechanical design:

Design of the electrical connection	• secondary side / for main current circuit	screw-type terminals
	• at the input / for main current circuit	screw-type terminals
Mounting type		screws
Construction form of the iron core		UI 180/75
Width	m	0.194
Height	m	0.32
Depth	m	0.169

Certificates/approvals:

General Product Approval	Shipping Approval	other	
	 GOST	 PRS	Declaration of Conformity other

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

CAX-Online-Generator

<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/4AT3632-8JD40-0FA0/all>

last change:

Dec 5, 2011