

TRANSFORMER SITAS;  
 PHASES:1;  
 PN/PN(S6)(KVA):8 /28,5;  
 UPRI(V):600-575-550-525-500- 480-460-440-415-400-240-230;  
 USEC(V):2X115;  
 ISEC(A):34,8-69,6;  
 F(HZ):50...60;  
 VECTOR GR./SHIELD WNG.:li0 /0;  
 TA/ISOKL:55 /H;  
 IP00;  
 TYPE OF TERMINALS:SCREW CONNECTION;  
 INSTALLATION:SCREW;  
 EN 61558-2-1, -2-2,  
 -2-4 >UL/CSA-RECOGNIZED< >CONTROL CIRCUIT  
 TRANSFORMER< >ISOLATION TRANSFORMER<

**General technical details:**

<b>Product designation</b>		transformer SITAS
<b>product brand name</b>		SIDAC
<b>Operating apparent output / rated value</b>	V-A	8,000
<b>Efficiency</b>		0.95
<b>Manner of switching for transformers</b>		li0
<b>Verification of suitability</b>		CE / cRUus
<b>Product function</b>		
• temperature surveillance		No
• isolation control		No
• short circuit and overload protection		No
<b>Number of the protective coils</b>		0
<b>Short-term vector power</b>	V-A	31,100
<b>Relative short-circuit voltage</b>	%	3.08

**Inputs:**

<b>Phase number / of the inputs</b>		1
<b>Input voltage</b>		
• _1 / rated value	V	600
• _2 / rated value	V	575
• _3 / rated value	V	550
• _4 / rated value	V	525
• _5 / rated value	V	500

• _6 / rated value	V	480
• _7 / rated value	V	460
• _8 / rated value	V	440
• _9 / rated value	V	415
• _10 / rated value	V	400
• _11 / rated value	V	240
• _12 / rated value	V	230
<b>Electrical input frequency</b>		
• minimum	Hz	50
• maximum	Hz	60

Outputs:		
<b>Phase number / of the outputs</b>		1
<b>Output voltage</b>		
• _1 / rated value	V	230
• _2 / rated value	V	115
<b>Electrical output frequency</b>		
• maximum	Hz	60
• minimum	Hz	50

Ambient conditions:		
<b>Thermal class / according to IEC 60085</b>		H
<b>Ambient temperature / rated value</b>	°C	55
<b>Protection class IP</b>		IP00

Mechanical design:		
<b>Design of the electrical connection</b>		
• secondary side / for main current circuit		screw-type terminals
• at the input / for main current circuit		screw-type terminals
<b>Mounting type</b>		screws
<b>Construction form of the iron core</b>		UI 210/70
<b>Width</b>	m	0.226
<b>Height</b>	m	0.37
<b>Depth</b>	m	0.174

Certificates/approvals:		
General Product Approval	Shipping Approval	other
		
		<a href="#">Declaration of Conformity</a> <a href="#">other</a>

**Further information:**

---

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/industrial-controls/catalogs>

---

**Industry Mall (Online ordering system)**

<http://www.siemens.com/industrial-controls/mall>

---

**CAX-Online-Generator**

<http://www.siemens.com/cax>

---

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<http://support.automation.siemens.com/WW/view/en/4AT3912-8ED40-0FA0/all>

---

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=4AT3912-8ED40-0FA0](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=4AT3912-8ED40-0FA0)

---

**last change:**

Dec 5, 2011