



POWER SUPPLY;
 PHASES:3;
 PN(KW):0,864;
 UPRI(V):575-500-460-400-230- 200;
 USEC(V DC):24;
 ISEC(A DC):36/43 (60/40 CEL);
 F(HZ):50...60;
 VECTOR GR./SHIELD WNG.:YY0 /0;
 PROTECTION CL.:I;
 TA/ISOKL:60 /B;
 W(%):4,2;
 IP00;
 TYPE OF TERMINALS:SCREW CONNECTION;
 INSTALLATION:SCREW;
 EN 61558-2-6,
 EN61131-2 >UL/CSA-RECOGNIZED< >SAFETY
 ISOLATING TRANSFORMER<

Inputs:

Design of the electrical connection / at the input / for main current circuit

screw-type terminals

Outputs:

Output voltage

- _1 / rated value

V

24

Output voltage / of the measured value signal / at the analog output / for DC / maximum

V

28.8

Output voltage / of the measured value signal / at the analog output / for DC / minimum

V

20.4

Output current

- _1 / rated value

A

36

Mechanical design:

Mounting type

screws

Certificates/approvals:

General Product Approval

Shipping Approval

other



[Declaration of](#)
[Conformity](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

CAX-Online-Generator

<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/4AV3402-2FB00-0C/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=4AV3402-2FB00-0C

last change:

Jul 7, 2014