



OUTPUT CHOKE; PHASES:3; UN1(V):460; ITHMAX 1(A) / F1(HZ):17,5 /120; F TAKT(KHZ):3; I LN (A):15,8; LN(MH):0,483; UK(%):2,4; TA/ISOKL:40 /B; IP00; TYPE OF TERMINALS:SCREW/TAB CONNECTION; EN 61558-2-20 >UL/CSA-RECOGNIZED<

Figure similar

General technical data:		
Product designation		output reactor
product brand name		SIDAC
Phase number		3
Type of voltage		AC
Operating voltage rated value		
• maximum	V	460
Operating frequency rated value		
• minimum	Hz	0
• maximum	Hz	120
Current		
• at AC		
— rated value	A	15.8
— maximum	A	17.5
Inductivity rated value	H	0.00048
Power loss [W] of the coil	W	60
Power loss [W] of the iron core	W	33.8

Clock frequency • rated value	Hz	3 000
---	----	-------

Mechanical data:

Type of electrical connection for main current circuit		screw-type terminals / tab terminals
Width	m	0.21
Height	m	0.17
Depth	m	0.12

Ambient conditions:

Thermal class acc. to IEC 60085		B
Ambient temperature rated value	°C	40
Protection class IP		IP00

Certificates/ approvals:

Declaration of Conformity	other
----------------------------------	--------------



EG-Konf.

[Bestätigungen](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrymall>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=4EP3900-3US00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/4EP3900-3US00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=4EP3900-3US00&lang=en

last modified:

10/07/2016