



OUTPUT CHOKE; PHASES:3; UN1(V):460; ITHMAX 1(A) / F1(HZ):260 /120; F TAKT(KHZ):3; I LN (A):234; LN(MH):0,016; UK(%):1,18; TA/ISOKL:40 /H; IP00; TYPE OF TERMINALS:FLAT-TYPE TERMINAL; EN 61558-2-20 >UL/CSA-RECOGNIZED<

Figure similar

General technical data		
Product designation		output reactor
Product brand name		SIDAC
Phase number		3
Type of voltage		AC
Operating voltage rated value		
• maximum	V	460
Operating frequency rated value		
• minimum	Hz	0
• maximum	Hz	120
Current		
• at AC		
— rated value	A	234
— maximum	A	260
Inductivity rated value	H	0.000016
Power loss [W] of the coil	W	161
Power loss [W] of the iron core	W	130

Clock frequency • rated value	Hz	3 000
---	----	-------

Mechanical data

Type of electrical connection for main current circuit		flat connector
Width	m	0.27
Height	m	0.24
Depth	m	0.18

Ambient conditions

Thermal class acc. to IEC 60085		H
Ambient temperature rated value	°C	40
Protection class IP		IP00

Certificates/ approvals

General Product Approval	other
---------------------------------	--------------

[Confirmation](#)



Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=4EU2731-3UA00-0A>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=4EU2731-3UA00-0A>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/4EU2731-3UA00-0A>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=4EU2731-3UA00-0A&lang=en

last modified:

04/14/2020