



COMMUTATING CHOKE FOR CONVERTER;
PHASES:3; UN1(V):400; ITHMAX 1(A) / F1(HZ):630
/50; I LN (A):567; UK(%):4; LN(MH):0,0334;
TA/ISOKL:40 /H; IP00; TYPE OF TERMINALS:FLAT-
TYPE TERMINAL; EN 61558-2-20 >UL/CSA-
RECOGNIZED< >CHOKE<

Figure similar

General technical data:		
Product designation		Kommut.-Drossel f. Stromrichter
Phase number		3
Type of voltage		AC
Operating voltage rated value	V	400
Operating frequency rated value	Hz	50
Current		
• at AC		
— rated value	A	567
— maximum	A	630
• at DC rated value	A	772
Peak current	A	788
Inductivity rated value	H	0.000033
Relative inductive drop in voltage on the measurement level current, voltage and frequency	%	4
Power loss [W] of the coil	W	293
Power loss [W] of the iron core	W	140

Mechanical data:

Type of electrical connection for main current circuit		flat connector
Width	m	0.35
Height	m	0.321
Depth	m	0.227

Ambient conditions:

Thermal class acc. to IEC 60085		H
Ambient temperature rated value	°C	40
Protection class IP		IP00

Certificates/ approvals:

General Product Approval	Declaration of Conformity	other
--------------------------	---------------------------	-------



EG-Konf.

[Bestätigungen](#)**Further information****Information- and Downloadcenter (Catalogs, Brochures,...)**<http://www.siemens.com/industrial-controls/catalogs>**Industry Mall (Online ordering system)**<http://www.siemens.com/industrymall>**Cax online generator**<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=4EU3622-1CA00-0AA0>**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**<https://support.industry.siemens.com/cs/ww/en/ps/4EU3622-1CA00-0AA0>**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=4EU3622-1CA00-0AA0&lang=en

last modified:

10/07/2016