SIEMENS

Product data sheet 4NC5113-0BC20



WINDOW-TYPE CURRENT TRANSFORMER, CLASS 3 60A/1A, 2,5VA PRIMARY CURRENT 60A, 2.5VA

Similar to image

General technical details:				
product designation		window-type current transformers		
Accuracy class / of the current transformer		class 3		
Ratio input current/output current		60/1 A		
Current				
• at the input / rated value	А	60		
• secondary side / rated value	А	1		
Operating apparent output / rated value	V-A	2.5		
Ambient temperature				
during operating	°C	-10 +55		
Item designation				
 according to DIN 40719 extendable after IEC 204-2 / according to IEC 750 		Т		
according to DIN EN 61346-2		Т		

Mechanical design:		
Width / of the push-through bus bar		
• in case of 1 bus bar / maximum	mm	12
Outer diameter / of the push-through conductor / maximum	mm	17.5
Protection class IP		IP20

Depth	mm	80
Height	mm	74.5
Width	mm	48
Type of mounting		screw fixing
Design of the electrical connection / secondary side		screw-type terminals
Product equipment / touch-protection		Yes

Certificates/approvals:

General Product Approval **Declaration of Conformity**





Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

http://www.siemens.com/lowvoltage/catalogs

Industry Mall (Online ordering system)

http://www.siemens.com/lowvoltage/mall

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

http://support.automation.siemens.com/WW/view/en/4NC5113-0BC20/all

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=4NC5113-0BC20

CAx-Online-Generator

http://www.siemens.com/cax

Tender specifications

Datanorm GAEB81 GAEB83 RTF TXT

last change: Dec 17, 2012