


# Linear actuator DLGF-G-40-400-PPSA

Part number: 5074740

**FESTO**



 General operating condition

## Data sheet

| Feature                                         | Value                                                              |
|-------------------------------------------------|--------------------------------------------------------------------|
| Stroke                                          | 400 mm                                                             |
| Piston diameter                                 | 40 mm                                                              |
| Cushioning                                      | Self-adjusting pneumatic end-position cushioning                   |
| Mounting position                               | Any                                                                |
| Guide                                           | Basic guide                                                        |
| Driver principle                                | Positive locking (slot)                                            |
| Position sensing                                | For proximity sensor                                               |
| Symbol                                          | 00995280                                                           |
| Operating pressure                              | 0.15 MPa ... 0.8 MPa                                               |
| Operating pressure                              | 1.5 bar ... 8 bar                                                  |
| Mode of operation                               | Double-acting                                                      |
| Operating medium                                | Compressed air as per ISO 8573-1:2010 [7:-:-]                      |
| Information on operating and pilot media        | Operation with oil lubrication possible (required for further use) |
| Corrosion resistance class (CRC)                | 1 - Low corrosion stress                                           |
| LABS (PWIS) conformity                          | VDMA24364-B1/B2-L                                                  |
| Ambient temperature                             | 0 °C ... 60 °C                                                     |
| Cushioning length                               | 12.9 mm                                                            |
| Max. force F <sub>y</sub>                       | 0 N                                                                |
| Max. force F <sub>z</sub> (towards actuator)    | 662 N                                                              |
| Max. force +F <sub>z</sub> (away from actuator) | 456 N                                                              |
| Max. torque M <sub>x</sub>                      | 7.7 Nm                                                             |
| Max. torque M <sub>y</sub>                      | 37.6 Nm                                                            |
| Max. torque M <sub>z</sub>                      | 11.2 Nm                                                            |
| Theoretical force at 6 bar, retracting          | 754 N                                                              |
| Theoretical force at 6 bar, advancing           | 754 N                                                              |
| Moving mass                                     | 450 g                                                              |
| Product weight                                  | 6456 g                                                             |
| Alternative connections                         | See product drawing                                                |
| Type of mounting                                | With accessories                                                   |
| Pneumatic connection                            | G1/4                                                               |
| Note on materials                               | RoHS-compliant<br>Copper-free                                      |
| Cover material                                  | Die-cast aluminum, coated                                          |

| Feature          | Value              |
|------------------|--------------------|
| Seals material   | NBR<br>TPE-U(PU)   |
| Housing material | Aluminum, anodized |