



# Vacuum generator VN-30-L-T6-PI5-VI6-RO2

Part number: 526132

**FESTO**



[General operating condition](#)

## Data sheet

| Feature                                       | Value                                         |
|-----------------------------------------------|-----------------------------------------------|
| Nominal width of Laval nozzle                 | 3 mm                                          |
| Width dimension                               | 24 mm                                         |
| Muffler construction type                     | Open                                          |
| Mounting position                             | Any                                           |
| Ejector characteristics                       | High suction rate<br>Standard                 |
| Integrated function                           | Pneumatic muffler open                        |
| Structural design                             | T-shape                                       |
| Symbol                                        | 00991489                                      |
| Operating pressure for max. suction rate      | 6 bar                                         |
| Operating pressure                            | 1 bar ... 8 bar                               |
| Nominal operating pressure                    | 6 bar                                         |
| Max. suction rate with respect to atmosphere  | 339 l/min                                     |
| Air supply time at nominal operating pressure | 0.1 s                                         |
| Operating medium                              | Compressed air as per ISO 8573-1:2010 [7:4:4] |
| Information on operating and pilot media      | Operation with oil lubrication not possible   |
| Corrosion resistance class (CRC)              | 2 - Moderate corrosion stress                 |
| LABS (PWIS) conformity                        | VDMA24364 zone III                            |
| Temperature of medium                         | 0 °C ... 60 °C                                |
| Noise level at nominal operating pressure     | 70 dB(A)                                      |
| Ambient temperature                           | 0 °C ... 60 °C                                |
| Max. tightening torque                        | 0.8 Nm                                        |
| Product weight                                | 183 g                                         |
| Type of mounting                              | With through-hole<br>With accessories         |
| Pneumatic connection 1                        | G1/4                                          |
| Pneumatic connection 3                        | Pneumatic muffler open                        |
| Vacuum connection                             | G3/8                                          |
| Material of connecting thread                 | Wrought aluminum alloy, anodized              |
| Note on materials                             | RoHS-compliant                                |
| Seals material                                | NBR                                           |
| Female nozzle material                        | POM                                           |
| Housing material                              | POM-reinforced                                |
| Muffler material                              | Die-cast aluminum<br>POM<br>PU foam           |
| Material of jet nozzle                        | Wrought aluminum alloy                        |