



# Air solenoid valve VMPA1-M1H-M-M7-PI

Part number: 533376

**FESTO**



 [General operating condition](#)

## Data sheet

| Feature                                      | Value                                                 |
|----------------------------------------------|-------------------------------------------------------|
| Valve function                               | 5/2, monostable                                       |
| Actuation type                               | Electrical                                            |
| Valve size                                   | 10 mm                                                 |
| Standard nominal flow rate                   | 360 l/min                                             |
| Pneumatic working port                       | M7                                                    |
| Operating voltage                            | 24V DC                                                |
| Operating pressure                           | 0.3 MPa ... 0.8 MPa                                   |
| Operating pressure                           | 3 bar ... 8 bar                                       |
| Structural design                            | Piston gate valve                                     |
| Reset method                                 | Pneumatic spring                                      |
| Certification                                | c UL us - Recognized (OL)                             |
| CE marking (see declaration of conformity)   | As per EU EMC directive<br>As per EU RoHS directive   |
| UKCA marking (see declaration of conformity) | To UK instructions for EMC<br>To UK RoHS instructions |
| Degree of protection                         | IP65<br>In mounted state<br>as per IEC 60529          |
| Exhaust air function                         | With flow control option                              |
| Sealing principle                            | Soft                                                  |
| Mounting position                            | Any                                                   |
| Manual override                              | Detenting<br>Non-detenting                            |
| Type of control                              | Pilot-controlled                                      |
| Pilot air supply port                        | Internal                                              |
| Flow direction                               | Non-reversible                                        |
| Symbol                                       | 00991050                                              |
| Lap                                          | Overlap                                               |
| Signal status display                        | yes                                                   |
| Pilot pressure MPa                           | 0.3 MPa ... 0.8 MPa                                   |
| Pilot pressure                               | 3 bar ... 8 bar                                       |
| Suitability for vacuum                       | no                                                    |
| Standard nominal flow rate with QS-6         | 360 l/min                                             |
| Switching time off                           | 20 ms                                                 |
| On switching time                            | 10 ms                                                 |
| Max. positive test pulse with 0 signal       | 400 µs                                                |
| Max. negative test pulse on 1 signal         | 200 µs                                                |

| Feature                                   | Value                                                                                |
|-------------------------------------------|--------------------------------------------------------------------------------------|
| Permissible voltage fluctuations          | +/- 25 %                                                                             |
| Operating medium                          | Compressed air as per ISO 8573-1:2010 [7:4:4]                                        |
| Information on operating and pilot media  | Operation with oil lubrication possible (required for further use)                   |
| Vibration resistance                      | Transport application test with severity level 2 as per FN 942017-4 and EN 60068-2-6 |
| Shock resistance                          | Shock test with severity level 2 as per FN 942017-5 and EN 60068-2-27                |
| Corrosion resistance class (CRC)          | 1 - Low corrosion stress                                                             |
| LABS (PWIS) conformity                    | VDMA24364-B1/B2-L                                                                    |
| Storage temperature                       | -20 °C ... 40 °C                                                                     |
| Temperature of medium                     | -5 °C ... 50 °C                                                                      |
| Relative air humidity                     | Max. 90 % at 40 °C                                                                   |
| Ambient temperature                       | -5 °C ... 50 °C                                                                      |
| Max. tightening torque for valve mounting | 0.25 Nm                                                                              |
| Product weight                            | 143 g                                                                                |
| Electrical connection                     | 4-pin<br>M8x1<br>Plug<br>as per EN 60947-5-2                                         |
| Type of mounting                          | With through-hole                                                                    |
| Pneumatic connection 1                    | M7                                                                                   |
| Pneumatic connection 2                    | M7                                                                                   |
| Pneumatic connection 3                    | M7                                                                                   |
| Pneumatic connection 4                    | M7                                                                                   |
| Pneumatic connection 5                    | M7                                                                                   |
| Note on materials                         | RoHS-compliant                                                                       |
| Seals material                            | NBR                                                                                  |
| Housing material                          | Die-cast aluminum                                                                    |