



# Regulator plate VABF-S3-1-R3C2-C-10

Part number: 543531

**FESTO**



 [General operating condition](#)

## Data sheet

| Feature                                  | Value                                                              |
|------------------------------------------|--------------------------------------------------------------------|
| Width                                    | 26 mm                                                              |
| Based on norm                            | ISO 15407-1                                                        |
| Mounting position                        | Any                                                                |
| Pneumatic vertical stacking              | Pressure regulator for 4                                           |
| Controller function                      | Outlet pressure constant<br>With secondary exhausting              |
| Symbol                                   | 00991579                                                           |
| Optional pressure gauge                  | Possible                                                           |
| Pressure regulation range MPa            | 0.2 MPa ... 0.85 MPa                                               |
| Pressure regulation range                | 2 bar ... 8.5 bar                                                  |
| Pressure regulation range psi            | 29 psi ... 123.25 psi                                              |
| Inlet pressure 1                         | 0.5 bar ... 10 bar                                                 |
| Operating medium                         | Compressed air as per ISO 8573-1:2010 [7:4:4]                      |
| Information on operating and pilot media | Operation with oil lubrication possible (required for further use) |
| Corrosion resistance class (CRC)         | 0 - No corrosion stress                                            |
| LABS (PWIS) conformity                   | VDMA24364-B1/B2-L                                                  |
| Degree of protection                     | IP65<br>NEMA 4                                                     |
| Ambient temperature                      | -5 °C ... 50 °C                                                    |
| Product weight                           | 305 g                                                              |
| Vertical stacking mounting type          | On manifold sub-base<br>On individual sub-base                     |
| Pressure gauge connection                | With retaining clamp                                               |
| Note on materials                        | RoHS-compliant                                                     |
| Material of operator panel               | PA                                                                 |
| Controller housing material              | Die-cast aluminum                                                  |