


Proximity sensor SME-8M-...-

Part number: 543892

FESTO



[PDF](#) General operating condition

Data sheet

Overall data sheet – Individual values depend upon your configuration.

Feature	Value
Symbol	00991619 00991620 00991621 00991622 00991624 00991989 00995366
Certification	RCM compliance mark c UL us - Listed (OL)
CE marking (see declaration of conformity)	As per EU EMC directive As per EU RoHS directive
UKCA marking (see declaration of conformity)	To UK instructions for EMC To UK RoHS instructions
Special features	Oil-resistant
Note on materials	RoHS-compliant Halogen-free
Application note	https://www.festo.com/Drive-Sensor-Overview
Measuring principle	Magnetic reed
Ambient temperature	-40 °C ... 70 °C
Switching output	Contact-based, bipolar
Switching element function	N/C contact N/O contact
Max. output current	80 mA ... 500 mA
Max. output current in mounting kits	80 mA
Min. switching capacity AC	2.4 VA ... 10 VA
Max. switching capacity DC	2.4 W ... 10 W
Max. switching capacity DC in mounting kits	2.4 W
Max. switching capacity AC in mounting kits	2.4 VA
Voltage drop	1.17 V ... 4.8 V
Short-circuit protection	no
Overload protection	Not available
Operating voltage range AC	5 V ... 30 V
DC operating voltage range	5 V ... 30 V
Reverse polarity protection	no
Electrical connection 1, connection type	Cable Cable with plug
Electrical connection 1, connection technology	M12x1 A-coded as per EN 61076-2-101 M8x1 A-coded as per EN 61076-2-104 Open end

Feature	Value
Electrical connection 1, number of pins/wires	2
Electrical connection 1, type of mounting	Snap-locking Screw-type lock rotatable not rotatable
Electrical connection 1, type of mounting	Compatible with latching lock Compatible with screw lock rotatable Compatible with rotatable/non-rotatable screw lock
Electrical connection for input 1, connection pattern	00991155 00991976 00992826 00995573 00997357
Connection outlet orientation	Longitudinal
Material of pin contacts	Copper alloy, gold-plated
Material of plug housing	TPE-U(PU)
Material of screw-type lock	Brass, nickel-plated
Connector cable test conditions	Flexural strength: as per Festo standard Test conditions on request Energy chain > 5 million cycles, bending radius 75 mm
Cable length	0.2 m ... 10 m
Cable characteristic	Standard/suitable for energy chains
Material of cable sheath	TPE-U(PUR)
Type of mounting	Can be inserted in slot from above
Product weight	8.9 g ... 87.1 g
Housing material	High-alloy stainless steel
Switching status indication	LED yellow
Ambient temperature with flexible cable installation	-5 °C ... 70 °C
Degree of protection	IP65 IP68
LABS (PWIS) conformity	VDMA24364-B2-L